

ITEM	PART#	DESCRIPTION	QTY	UOM
A,B	39014043	MiniFitJrPlg SR PnlMnt V-0 4 Ckt	2	PC
C	39000095	MiniFit Term Crp Male C Bs Au 16awg	8	PC
D	--	PAPER PRINTED PAPER WHITE	1	PC

FROM	TO	DESCRIPTION	COLOR
A1	B4	1X16AWG DISC PVC BK UL1015 HOOKUP	BLACK
A2	B3	1X16AWG DISC PVC BK UL1015 HOOKUP	BLACK
A3	B2	1X16AWG DISC PVC BK UL1015 HOOKUP	BLACK
A4	B1	1X16AWG DISC PVC BK UL1015 HOOKUP	BLACK




TABLE			
PART NUMBER	L1	L2	TITLE
2153222041	150±8	63 REF	MINIFIT JR SR M-M 4 CIRCUIT 150MM Au
2153222042	300±10	138 REF	MINIFIT JR SR M-M 4 CIRCUIT 300MM Au
2153222043	600±10	288 REF	MINIFIT JR SR M-M 4 CIRCUIT 600MM Au

NOTES

1. Cable assembly must pass 100% continuity and polarity test.
2. Connector view shown is from mating side.
3. Label text must be 2mm max. in height with Arial font.
4. Label must be wrapped in flag type on a single cable.

MOLEX P/N
MOLEX
BATCH WK/YR

DETAIL A

REVISION			
DATE	REV	DESCRIPTION	CHANGER
2020/03/23	A	INITIAL RELEASE	ARAJU

FUNCTIONAL SYMBOLS $\frac{E}{A} = 0$ $\frac{E}{E} = 0$ $\frac{E}{P} = 0$ DIVISIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC:		
	DIMENSION UNITS	SCALE	GENERAL TOLERANCES (UNLESS SPECIFIED)		
	mm	NTS	ANGULAR TOL ± °		
	4 PLACES ±		EC NO: 638380		
3 PLACES ±		DRWN: ARAJU 2020/03/05		PRODUCT CUSTOMER DRAWING DOCUMENT NUMBER: 2153222041 DOC TYPE: PSD DOC PART: 000 REVISION: A	
2 PLACES ±		CHK'D: RDESAI01 2020/05/28			
1 PLACE ±		APPR: RDESAI01 2020/05/28			
0 PLACES ±		INITIAL REVISION: DRWN: ARAJU 2020/03/05 APPR: RDESAI01 2020/05/28		MATERIAL NUMBER: SEE TABLE CUSTOMER: GENERAL MARKET SHEET NUMBER: 1 OF 1	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING: A4-SIZE		SERIES: 215322