





THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN CHOGORI PERSONNEL WITHOUT AUTHORIZATION FROM CHOGORI CORP.

REV.	ECN NO.	DESCRIPTION	SIGN	DATE
C1	N/A	INITIAL DRAWING	Hary	2020/05/18



- Specification:
- 1.Operation Temperature: -45°C~105°C.
 - 2.Insulation Resistance:100MΩ at DC500V.
 - 3.Contact Resistance:<10mΩ.
 - 4.Withstand Voltage: 1500V AC
 - 5.Operating Current:10A
 - 6.Operating Voltage:AC 125V
 - 7.Waterproof Rate:IP67 (Mated)
 - 8.Seal Nut:Nylon, Black
 - 9.Seal Ring:Silicon, Black.
 - 10.Clamp Ring:Nylon, Black
 - 11..Gasket:Silicon, Red
 - 12.Female Pin:Copper Alloy, Gold Plated
 - 13.Connector:Nylon+GF, Black
 - 14.Lock Nut:Nylon, Orange
 - 15.Spring:SUS
 - 16.O-Ring:Silicon, Red
 - 17.RoHS Compliant.
 - 18.UL Compliant.
 - 19.Mating Cap:804-00007-00

23XXX231-XX Cable Range OD
 01 OD: φ3.5mm~φ6.5mm
 02 OD: φ6.5mm~φ9.5mm
 Pin Number

5 Pin	6 Pin
P/N: 23005231-XX	P/N: 23006231-XX
Pin Assignments Front View	

UNIT:mm		DESCRIPTION	Middle Series Push Lock Male Plug With Female Pin	
TOLERANCE	.X ±0.25 .XX ±0.15 .XXX ±0.05 ANGLES ±1°	SCALE:	1:1	SHEET 1 OF 1
REV.	C1	SIZE	A4	* :Inspection Item



PART NO	23XXX231-XX	DRAWN BY	Hary	DATE	2020/05/18
DWG NO		CHECKED BY	Mo	DATE	2020/05/18
CUSTOMER		APPROVED BY	Panson	DATE	2020/05/18

1 2 3 4 5 6 7 8