



- NOTES
- ① PLATING (REF. NO. ②, ③)  
 CONTACT AREA : GOLD PLATING 0.2μm min.  
 LEAD AREA : GOLD PLATING FLASH.  
 UNDER PLATING: NICKEL PLATING 2μm min.
  - ② RECOMMENDED TIGHTENING TORQUE OF REF. NO. ⑦ : 0.8 N·m.  
 LOOSENED NUT MAY CAUSE THE DETERIORATION OF WATER-RESISTANCY.  
 THE USE OF LOOSENING-PREVENTIVE ADHESIVE IS STRONGLY RECOMMENDED.  
 RECOMMENDED THREAD LOCKER : LOCTITE 263, LOCKPRIMER 7649, HENKEL JAPAN LTD.
  - ③ AFTER REF. NO. ⑤ IS INSERTED TO REF. NO. ①,  
 REF. NO. ① IS MOUNTED ON THE PANEL.  
 MAKE SURE THAT REF. NO. ⑤ DOES NOT HAVE ANY FACTORS TO REDUCE WATER-RESISTANCY,  
 SUCH AS SCRATCH, TWIST, PINCHING, OR DUST.

4	PPS	(BLACK) UL94V-0			
3	PHOSPHOR BRONZE	①	7	BRASS	NICKEL PLATING
2	PHOSPHOR BRONZE	①	6	PHOSPHOR BRONZE	NICKEL PLATING
1	PPS	(BLACK) UL94V-0	5	CR	(BLACK)
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS		SCALE	COUNT	DESCRIPTION OF REVISIONS	
mm		5 : 1	△	DESIGNED	CHECKED
HRS		HIROSE ELECTRIC CO., LTD.	APPROVED : HY. KOBAYASHI	18.03.12	DRAWING NO. EDC-113486-31-00
			CHECKED : HY. KOBAYASHI	18.03.12	PART NO. HR30-8R-12S(31)
			DESIGNED : DS. MATSUNE	18.03.12	CODE NO. CL130-1018-1-31
			DRAWN : DS. MATSUNE	18.03.12	