

## R66ED3150JB7AJ

Aliases (66ED3150JB7AJ)

R66, Film, Metallized Polyester Stacked, Automotive Grade, 0.15 uF, 5%, 100 VDC, 85°C, Lead Spacing = 7.5mm



Click [here](#) for the 3D model.

### Dimensions

|    |                 |
|----|-----------------|
| L  | 10mm +0.2mm     |
| H  | 8mm +0.1mm      |
| T  | 3mm +0.1mm      |
| S  | 7.5mm +/-0.4mm  |
| LL | 3.5mm +0.5mm    |
| F  | 0.5mm +/-0.05mm |

### Packaging Specifications

|                    |      |
|--------------------|------|
| Packaging          | Bulk |
| Packaging Quantity | 1500 |

### General Information

|                |                                                  |
|----------------|--------------------------------------------------|
| Series         | R66                                              |
| Dielectric     | Metallized Polyester Stacked                     |
| Style          | Radial                                           |
| Features       | Automotive Grade, DC Multipurpose Applications   |
| RoHS           | Yes                                              |
| Lead           | Cut                                              |
| Qualifications | AEC-Q200                                         |
| AEC-Q200       | Yes                                              |
| Miscellaneous  | Above 85C DC And AC Voltage Derating Is 1.25%/C. |

### Specifications

|                       |                     |
|-----------------------|---------------------|
| Capacitance           | 0.15 uF             |
| Capacitance Tolerance | 5%                  |
| Voltage AC            | 63 VAC              |
| Voltage DC            | 100 VDC             |
| Temperature Range     | -55/+105°C          |
| Rated Temperature     | 85°C                |
| Dissipation Factor    | 1% 1kHz, 1.5% 10kHz |
| Insulation Resistance | 3.75 GOhms          |
| Max dV/dt             | 150 V/us            |
| Inductance            | 8 nH                |