



4-40 THREAD STANDOFF ENGINEERING KIT CAT. NO. STR-440				
HEX. =	Threaded Female		Threaded Male/Female	
	Aluminum	Nylon	Aluminum	Nylon
Length	Cat. No.	Cat. No.	Cat. No.	Cat. No.
.250 [6.35]	2201	1902A	8714	4800
.500 [12.70]	2203	1902C	8401	4802
.750 [19.05]	2204	1902D	8403	4804
1.00 [25.40]	2205	1902E	8405	4806
Cat. No. 9900 4-40 x 1/4" Phillips Drive Machine Screw				



NOTES:

1. A KIT HAS 25 PIECES OF EACH CAT.NO. FOR A TOTAL QUANTITY OF 425 PIECES AND IS HOUSED IN A 16 TRAY, LABELED ENCLOSURE.
2. MAT'L - ALUMINUM, CLEAR IRIDITE
MAT'L - NYLON 6/6
3. DRAWS WILL BE ASSEMBLED WITH PLASTIC DIVIDER INSTALLED AND PRODUCT PLACED IN THE FRONT PORTION OF EACH DRAW.
4. SCREWS TO BE PLACED IN THE BACK PORTION OF THE UPPER LEFT MOST DRAW BEHIND THE 1/4" OR 3/8" L. ALUMINUM STANDOFFS.

KEYSTONE ELECTRONICS CORP.			
www.keyelco.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500			
PART NAME			
4-40 THREAD , .250 HEX STANDOFF KIT			
MATERIAL			
AS NOTED			
FINISH		DRN BY	DATE
AS NOTED		NT	2.22.19
		APP'D	SCALE
		LN	-
TOLERANCES	INCH	[MM]	CODE
DECIMAL	±	[±]	C
ANGULAR	±		
UNLESS OTHERWISE SPECIFIED			DWG NO.
			CTR-440

DATE	DESCRIPTION	REV.