



WIRE LIST:

P1		P2
1	RED	1
2	WHITE	2
3	GREEN	3
4	BLACK	4
	BRAID+DRAIN	SHELL

P/N	XX(FT)	L(MM)	TOLERANCE(MM)
U024-06N-PM	06INCH	152.4	+15/-0
U024-001-PM	01	300	+15/-15
U024-002-PM	02	610	+25/-25
U024-006-PM	06	1800	+75/-51

NOTE:

- CABLE:UL2725 USB 2.0 CABLE 28AWG*1P+20AWG*2C+AEB(AL) OD: φ4.8mm BLACK PVC JACKET.
- CONNECTOR:
 P1: USB A TYPE MALE, SOLDED TYPE,WHITE PBT INSULATIPON,GOLD PLATED CONTACTS, NICKEL PLATED SHELL.
 P2 :USB A TYPE FEMALE, SOLDED TYPE,WHITE PBT INSULATIPON,GOLD PLATED CONTACTS, NICKEL PLATED SHELL.
- MOLDING: P1:MOLDING 45P BLACK PVC,P2:MOLDING 25P BLACK PVC.
- MOLD NO.: USB-AM01,USB-AF03.
- CABLE ASS'Y MUST PASS CONTINUITY TEST.

B1	Increase external mold size		07/27/15				
B	Add Length:2FT		11/05/13				
A	INITIAL RELEASE		01/19/13				
REV	DESCRIPTION OF CHANGE		DATE				
TOLERANCE							
INCHES							
M/M							
.X	.015	.30	SCALE	NONE		REV	B1
.XX	.010	.10	UNIT	MM			
.XXX	.005	.05	SHEET	1/1	DWG NO.		
DRAWN BY	CAI		DATE	07/27/15			
CHECK BY			TITLE USB A M TO USB A F				
APPD BY			PART NO. U024-XXX-PM				

