

**LINEAR TECHNOLOGY MATERIALS DECLARATION**

1tc2607cde#trpbf

(Engineering Calculation)

DFN 4mm X 3mm Exp. Pad

(printed on: 2020-07-11 21:56:20)

**TOTAL MASS (g) : 0.031326**

COMPONENT MATERIAL	VENDOR/ INDUSTRY NAMES	CONSTITUENT NAME	CAS NUMBER	CONSTITUENT MASS (g)	CONSTITUENT (PPM) OF MATERIAL	CONSTITUENT (PPM) OF TOTAL PKG.		
Active Device	Linear Technology	Silicon (Si)	7440-21-3	0.001648	1000000	52608.3320312		
Die Coat	Dow Corning	Silicone	69430-27-9	0.000000	0	0		
Lead Frame	Cu	Copper (Cu)	7440-50-8	0.012783	975000	408065.75		
		Iron (Fe)	7439-89-6	0.000315	24000	10055.5976562		
		Phosphorus (P)	7723-14-0	0.000004	300	127.690132141		
		Zinc (Zn)	7440-66-6	0.000009	700	287.30279541		
		Nickel (Ni)	7440-02-0	0.000000	0	0		
		Silicon (Si)	7440-21-3	0.000000	0	0		
		Magnesium (Mg)	7439-95-4	0.000000	0	0		
		Tin (Sn)	7440-31-5	0.000000	0	0		
<b>Lead Frame Total:</b>				<b>0.013111</b>	<b>1000000</b>	<b>418536.3125</b>		
Plating	PMI	Exter. Plating Pb	7439-92-1	0.000000	0	0		
		Exter. Plating Sn	7440-31-5	0.000607	1000000	19371.6992188		
		<b>External Plating Total:</b>				<b>0.000607</b>	<b>1000000</b>	<b>19371.6992188</b>
		Inter. Plating Ni	7440-02-0	0.000000	0	0		
		Inter. Plating Ag	7440-22-4	0.000295	1000000	9417.14746094		
<b>Internal Plating Total:</b>				<b>0.000295</b>	<b>1000000</b>	<b>9417.14746094</b>		
Die Attach	ELECTRICALLY CONDUCTIVE ADHESIVE	Silver (Ag)	7440-22-4	0.000798	750000	25474.1816406		
		Tin (Sn)	7440-31-5	0.000000	0	0		
		Lead (Pb)	7439-92-1	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.000000	0	0		
		Indium (In)	7440-74-6	0.000000	0	0		
		Metal Oxide		0.000000	0	0		
		Antimony (Sb)	7440-36-0	0.000000	0	0		
		Resin (EP)		0.000266	250000	8491.39355469		
<b>Die Attach Total:</b>				<b>0.001064</b>	<b>1000000</b>	<b>33965.5742188</b>		
Encapsulation	MULTI-AROMATIC RESIN Br/Sb FREE	Resin (EP)		0.001888	130000	60269.7421875		
		Bromine (Br)	40039-93-8	0.000000	0	0		
		Silica (SiO2)	60676-86-0	0.012487	860000	398616.65625		
		Antimony Trioxide (Sb2O3)	1309-64-4	0.000000	0	0		
		Metal Hydroxide		0.000000	0	0		
		Carbon Black (C)	1333-86-4	0.000145	10000	4628.76708984		
		<b>Encapsulation Total:</b>				<b>0.014520</b>	<b>1000000</b>	<b>463515.15625</b>
Bond Wire Estimated	AFW/TANAKA/ Kn	Gold (Au)	7440-57-5	0.000081	1000000	2585.72509766		
					<b>TOTAL MASS (g) :</b>	<b>0.031326</b>		