HellermannTyton

Specification Sheet

Part Number: 166-90308

HelaGuard Non-Metallic IP66 Fitting, Straight, 2" NPT Thread, 2" Dia., PA66, Black, 1/pkg

Article Number	166-90308
Type	HG200-S-2000
Color	Black (BK)
Features & Benefits	•External NPT thread provides a secure connection. •Snap-on construction reduces installation time and costs by eliminating the need to thread fittings onto conduits. •All-around "teeth" attach firmly to conduit and deliver a high extraction force. •Durable nylon material has high resistance to salts, oils, weak acids and solvents. •IP66 fitting has one-piece construction.
Quantity Per	bag
Product Description	Straight fitting features a snap-on design that provides a quick, secure connection. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Designed for easy removal with a small screwdriver. IP66 ingress protection rated fittings.

Short Description	HelaGuard Non-Metallic IP66 Fitting, Straight, 2" NPT Thread, 2" Dia., PA66, Black, 1/pkg
Global Part Name	HG200-S-2000-PA66-BK
Length L (Imperial)	2.91
Length L (Metric)	74
Variant	Straight
Outside Diameter OD(Imperial)	3.54
Outside Diameter OD(metric)	90
Nominal Diameter (Imperial)	2-5/8
Nominal Diameter (Metric)	67
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V2
Halogen free	Yes
Operating Temperature (Metric)	-58°F to +275°F (-50°C to +135°C)
Reach Complaint(Article 33)	Yes

ROHS Complaint	Yes
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity(Imperial)	2
Package Quantity (Metric)	1
Customs Number	3926909988

Contact Us   RoHS/WEEE Compliance   Disclaimer   Terms and Conditions