



POLE	MATERIAL NUMBER	ENGINEERING NUMBER	FINISHED LENGHT IN/MM
3	1200280677	443030E03M006	1.97' +1.75" -0 [0.6M +44.5 -0]
3	1200280678	443030E03M010	3.28' +2.19" -0 [1.0M +55.6 -0]
3	1200281285	443030E03M020	6.56' +3.50" -0 [2.0M +88.9 -0]
4	1200280941	444030E03M006	1.97' +1.75" -0 [0.6M +44.5 -0]
4	1200280899	444030E03M010	3.28' +2.19" -0 [1.0M +55.6 -0]
4	1200281293	444030E03M020	6.56' +3.50" -0 [2.0M +88.9 -0]

CONNECTOR SPECIFICATION:	
VOLTAGE RATING	3-4POL:60V/AC 75V/DC
AMPERAGE RATING	3 AMPS
PROTECTION	IP68
OPERATING TEMPERATURE	-30°C TO +80°C
UL CERTIFICATIONS	UL listed, File #E152210
CSA CERTIFICATIONS	CSA CERTIFIED, File LR6837

ITEM	COMPONENT	MATERIAL	FINISH
1	INSERT	POLYURETHANE (PUR)	BLACK
2	CONTACT SOCKET	COPPER ALLOY	GOLD OVER NICKEL
3	COUPLING NUT	BRASS	NICKEL PLATED
4	OVERMOLD	TPU	YELLOW
5	O-RING	VITON	
6	CABLE- 24 AWG, (COPPER STRANDING) 3/4 CONDUCT. 300V	JACKET:PVC	BLACK

DESCRIPTION	EC NO: WEU2010-0330	2010/02/04	DRWN: REISSNER	2010/02/04	CH'KD: FP	2010/02/11	APPR: NSTAUDIG	2010/02/11
QUALITY SYMBOLS	$\nabla = 0$	$\nabla = 0$						

	GENERAL TOLERANCES (UNLESS SPECIFIED)	
	mm	INCH
4 PLACES	$\pm .01$	$\pm .0005$
3 PLACES	$\pm .02$	$\pm .001$
2 PLACES	$\pm .04$	$\pm .002$
1 PLACE	$\pm 0.3$	$\pm .01$
ANGULAR $\pm \dots^\circ$		

DRAWN BY		DATE	
REISSNER		2010/02/04	
CHECKED BY		DATE	
FP		2010/02/04	
APPROVED BY		DATE	
NSTAUDIG		2010/02/10	

SCALE		DESIGN UNITS		THIRD ANGLE PROJECTION	
2:1		METRIC			
NC 3/4P M/MFE XM ST/ST AWG 24 PVC					
MOLEX INCORPORATED					
MATERIAL NO.				DOCUMENT NO.	
SEE TABLE				SD-120087-024	
SIZE A3				SHEET NO. 1	