

CTCH108F Series

From 10 μ H to 1,000 μ H



SPECIFICATIONS

Part numbers indicate available inductance tolerance.
K = $\pm 10\%$, M = $\pm 20\%$

| Part Number | Inductance (μ H) | Test Freq. (Hz) | DCR Max. (Ω) | Rated DC (A) |
|---------------|-----------------------|-----------------|-----------------------|--------------|
| CTCH108F-100M | 10 | 2.52M | 0.027 | 4.50 |
| CTCH108F-120M | 12 | 2.52M | 0.031 | 4.10 |
| CTCH108F-150M | 15 | 2.52M | 0.036 | 3.70 |
| CTCH108F-180M | 18 | 2.52M | 0.049 | 3.40 |
| CTCH108F-220M | 22 | 2.52M | 0.055 | 3.10 |
| CTCH108F-270M | 27 | 2.52M | 0.062 | 2.80 |
| CTCH108F-330K | 33 | 2.52M | 0.079 | 2.50 |
| CTCH108F-390K | 39 | 2.52M | 0.087 | 2.30 |
| CTCH108F-470K | 47 | 2.52M | 0.099 | 2.10 |
| CTCH108F-560K | 56 | 2.52M | 0.130 | 1.90 |
| CTCH108F-680K | 68 | 2.52M | 0.140 | 1.70 |
| CTCH108F-820K | 82 | 2.52M | 0.160 | 1.60 |
| CTCH108F-101K | 100 | 1.00k | 0.210 | 1.40 |
| CTCH108F-121K | 120 | 1.00k | 0.240 | 1.30 |
| CTCH108F-151K | 150 | 1.00k | 0.320 | 1.20 |
| CTCH108F-181K | 180 | 1.00k | 0.350 | 1.10 |
| CTCH108F-221K | 220 | 1.00k | 0.450 | 0.96 |
| CTCH108F-271K | 270 | 1.00k | 0.610 | 0.87 |
| CTCH108F-331K | 330 | 1.00k | 0.690 | 0.79 |
| CTCH108F-391K | 390 | 1.00k | 0.780 | 0.72 |
| CTCH108F-471K | 470 | 1.00k | 1.000 | 0.66 |
| CTCH108F-561K | 560 | 1.00k | 1.200 | 0.60 |
| CTCH108F-681K | 680 | 1.00k | 1.400 | 0.55 |
| CTCH108F-821K | 820 | 1.00k | 1.800 | 0.50 |
| CTCH108F-102K | 1000 | 1.00k | 2.100 | 0.45 |

CHARACTERISTICS

Description: Radial leaded fixed inductor

Applications: High reliability, efficiency and saturation. Ideal for use as a power choke coil in switching power supply, TV sets, video appliances, and industrial equipment as well as use as a peaking coil in filtering applications

Inductance Tolerance: $\pm 10\%$, $\pm 20\%$

Testing: Tested on a HP4285A or HP4284A at specified frequency

Packaging: Bulk packaging

Rated Current: The rated D.C. current indicates the value of current when the inductance is 10% lower than its initial value at D.C. superposition or D.C. current when at $\Delta t=40^\circ\text{C}$, whichever is lower. ($T_a=20^\circ\text{C}$)

Miscellaneous: RoHS Compliant

Additional Information: Additional electronic & physical information available upon request

Samples available. See website for ordering information.

PHYSICAL DIMENSIONS

| Size | A | B | C | D | E | F |
|--------|-----------------|-----------------|-------------------|------------------|-----------------|------------------|
| mm | 8.0 \pm 0.5 | 3.5 \pm 1.0 | 0.7+0.1,-0.05 | 4.0 \pm 0.3 | 10.0 \pm 0.5 | 5.0 \pm 0.3 |
| inches | 0.31 \pm 0.02 | 0.14 \pm 0.04 | 0.027+0.04,-0.002 | 0.16 \pm 0.012 | 0.40 \pm 0.02 | 0.20 \pm 0.012 |

