



WIRING SCHEMATIC

VOLTAGE RATING:	300V
AMPERAGE RATING:	max. 4A
PROTECTION CLASS:	IP 68
OPERATING TEMPERATURE:	FLEXING -5°C TO +80 °C STATIC -30 °C TO +80 °C

1200800004	WW4A30A09M020	6.56' +3.50" -0 [2.0M +88.9 -0]
1200800003	WW4A30A09M010	3.28' +2.19" -0 [1.0M +55.6 -0]
1200800002	WW4A30A09M006	1.97' +1.75" -0 [0.6M +44.5 -0]
1200800001	WW4A30A09M003	0.98' +0.75" -0 [0.3M +19.1 -0]
MATERIAL NUMBER	ENGINEERING NUMBER	FINISHED LENGTH

ITEM	COMPONENT	MATERIAL	FINISH
7	LABEL	MYLAR	BLACK/YELLOW
6	O-RING	VITON	GREEN
5	ULTRA-LOCK	BRASS	NICKEL PLATED
4	CONTACT	COPPER ALLOY	Au OVER Ni
3	INSERT	PUR	BLACK
2	OVERMOLD	PVC	YELLOW
1	CABLE #22	PVC	YELLOW

ENTER DESCRIPTION EC NO: WEU2010-0333 DRAWN: APOHL_WEU 2010/02/10 CHKD: REISSNER 2010/02/11 APPR: FPACHER 2010/02/25	QUALITY SYMBOLS ▽=0 ◻=0
--	-------------------------------

GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE IN/MM
4 PLACES ± --- ± ---	DRAWN BY DATE
3 PLACES ± --- ± ---	CHECKED BY DATE
2 PLACES ± --- ± 0.1	REISSNER 2010/02/11
1 PLACE ± 0.3 ± ---	APPROVED BY DATE
ANGULAR ± ---°	FPACHER 2010/02/24
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	MATERIAL NO. DOCUMENT NO.

SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
IN/MM	METRIC	⊙ □
TITLE	MIC INL. SPLITTER XM PVC STR	
SEE NOTES	MOLEX INCORPORATED	
SIZE A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	SHEET NO. 1 OF 1