

## KX15 Series Angle Type Production Site Relocation

JAE's KX15 series angle type production site will change from a JAE production facility in the Philippines to Japan. This relocation will happen immediately. Please see details below.

### 1. Applicable Products

KX15-50KLDLE, KX15-50KLDL-E1000E

\*Only applicable for 50 pin. There is no change in other types.

### 2. Relocation

Production site to change from Philippines to Japan.

### 3. Scheduled Relocation

- Production in Japan will start immediately
- Please consult your JAE account representative for information on the specific lot number and where it is manufactured if necessary


### 4. Modification Information

The KX15 series angle type's appearance will be modified. Please see below.

| Modification Details | Before                        | After                            | Reason   |
|----------------------|-------------------------------|----------------------------------|--|
| Country of origin    | Philippines                   | Japan                            | Exterior box and label changed                                       |
| Contact              | Phosphor bronze<br>C5102R-H   | Phosphor bronze<br>C5210R-H      | Japan material availability (to use contacts with other pin numbers) |
| Insulator *          | Lightening inside mating part | No lightening inside mating part | To support use of existing mold                                      |
| Reel *               | Plastic                       | Paper                            | Standard material used in new location                               |
| Lot number display * | K***                          | B***                             | Change of production plant   |

Please see next page for further details.

## Appearance Changes:

|                                | Before  | After  |
|--------------------------------|---|--|
| <b>Insulator</b><br>Lightening |  <p>Before<br/>Lightening Done</p>                             |  <p>After<br/>No Lightening</p>                              |
| <b>Lot Number Display</b>      |  <p>Before<br/>Starts with "K"</p>                             |  <p>After<br/>Starts with "B"</p>                            |
| <b>Reel</b>                    | Plastic Reel<br>Outer Diameter $\Phi 380$<br>Color Black<br> | Paper Reel<br>Outer Diameter $\Phi 370$<br>Color White<br> |

## 5. Evaluation Testing

Reliability tests have been completed with other pin counts. (30 pins and 80 pins)

\*Please contact your JAE account manager if there are any requests for 4M applications from customers or if adjustment of the detailed specifications with the customer is needed.

If you have any questions regarding this matter, please contact your JAE account manager.

Thank you for your cooperation.

