




Data sheet | Item number: 757-244/000-010
M12 sensor/actuator box; 4-way; 4-pole; 10 m

www.wago.com/757-244/000-010



i Picture differs from the item.



Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Item description

- M12 sensor/actuator box, 4-way
- 4-pole (1 signal per contact)
- Cable length: 5 and 10 m
- Green LED operating indicator
- Yellow LED status indicator
- incl. markers (10 pcs)
- incl. M12 protective caps (2 pcs)

Data

Technical data

Contact resistance (max.)	0.01 Ω
Supply voltage	10 ... 30 VDC; Rated voltage: 32 V ~ rms
Current carrying capacity (signal connections)	2 A
Current carrying capacity (supply connections)	9 A
Rated value of electrical isolation	500 V
Functionally separated potential groups	Kontakt/Kontakt
Insulation resistance	1000 M Ω
Signal characteristics	PNP
Indicators	LED (A) yellow: Signal status (1 x per contact); LED (U) green: Sensor /actuator box status

Connection data

Connection technology: inputs/outputs	4 x M12 socket; 4-pole; incl. ground
Connection technology: trunk cable	1 x Fixed connecting cable
Length of connection cable	10 m
Strip length	100 mm / 3.94 inches
Wire colors	white, green, yellow, gray, green/yellow, brown, blue
Cable design	Wire cross-section: 0.34 mm ² ; Wire cross-section (2): 1 mm ²

Physical data

Width	60 mm / 2.362 inches
Height	26 mm / 1.024 inches
Depth	117 mm / 4.606 inches

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.

Mechanical Data

Mounting type	Screw mounting
Weight	988 g

Material Data

Housing material	PA 66 (UL 94 V0); RAL 7035; silicon and halogen free
Halogen-free	Yes
Sheathed cable diameter	7.5 mm
Bending radius	10 x cable diameter (min.) for flexible application
Material properties of the connections	Contact: CuSn, nickel base-coat plating and 0.8 µm gold-plated; Threaded bush: die-cast Zn, nickel-plated; Seal: Viton; 50 mating cycles
Sheath material	PUR
Sheathed cable color	black
Encapsulation	Fully encapsulated with conformal coating (UL 94 V0)

Environmental requirements

Ambient temperature (operation)	-25 ... +80 °C
Ambient (operating) temperature (dynamic)	-5 ... +80 °C
Ambient (operating) temperature (static)	-40 ... +80 °C
Protection type	IP68
Note on protection type	72 h at a depth of 1 m under water per EN 60529 in the fully locked position with its plugs or protective caps
Pollution degree	3 per VDE 0110
Vibration resistance	per IEC 60068-2-6
Shock resistance	per IEC 60068-2-27

Commercial data

Product Group	23 (I/O passive and accessories)
eCl@ss 10.0	27-44-01-08
eCl@ss 9.0	27-44-01-08
ETIM 8.0	EC002585
ETIM 7.0	EC002585
PU (SPU)	1 pcs
Packaging type	box
Country of origin	DE
GTIN	4045454028282

Subject to changes. Please also observe the further product documentation!


Customs tariff number	85366990990
-----------------------	-------------

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	a3929a91-faa3-4eda-a41d-9c6bd9473d6f
SCIP notification number (Belgium)	829e7725-9eeb-4803-8587-922c9be14ac6
SCIP notification number (Bulgaria)	ec886539-e203-4916-89ec-cfea053df5a7
SCIP notification number (Czech Republic)	87dfbb59-6ee3-494f-99e7-9f95557c1876
SCIP notification number (Denmark)	a79fb81e-cdd8-4e02-9f60-ce0e2492395a
SCIP notification number (Finland)	f63f84c2-ea02-447d-b462-9534c2bff76b
SCIP notification number (France)	0bb898e3-4def-4e42-b6bd-bda3475090e7
SCIP notification number (Germany)	f80f9f95-38bd-4815-b355-472e174ceb43
SCIP notification number (Hungary)	23bec2a2-12da-46de-8ac6-8ac707513a74
SCIP notification number (Italy)	80de0836-9a0f-4f8d-bc19-c7582b28557f
SCIP notification number (Netherlands)	ac5f637a-e76f-4baa-9226-81829e08f852
SCIP notification number (Poland)	0fc71859-356a-4820-b196-ea7ea5e70b7f
SCIP notification number (Romania)	c5958a5f-4b2a-4675-bda5-2308492180d4
SCIP notification number (Sweden)	408c9a5e-70f9-4237-abbe-a1d4067a7a5c

Approvals / Certificates

General approvals

Logo	Approval	Additional Approval Text	Certificate name
	UL UL International Germany GmbH (ORDINARY LOCATIONS)	UL 508	E175199 Sec.5

Optional accessories

Marking accessories

Marking strip



Item no.: 757-011

Marker card; not stretchable; snap-on type

www.wago.com/757-011

Marking devices

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

	Item no.: 210-110 Fiber-tip pen	www.wago.com/210-110
Mounting		
Intermediate plate		
	Item no.: 757-040 Spacer module for sensor/actuator box; 4-way	www.wago.com/757-040
Cover		
Cover		
	Item no.: 756-8102 M12 protective cap; for unused sockets	www.wago.com/756-8102

Downloads

Documentation

System Description

Sensor/Actuator Boxes – General Product Information	pdf 438.6 kB	Download
---	-----------------	----------

Additional Information

Disposal and Recycling	V 1.1.0 2022 Aug 18	pdf 2.2 MB	Download
Electrical and electronic equipment, Batteries, Packaging			

CAD/CAE-Data

CAE data

EPLAN Data Portal 757-244/000-010	URL	Download
WSCAD Universe 757-244/000-010	URL	Download
ZUKEN Portal 757-244/000-010	URL	Download
WSCAD Universe 757-244/000-010	URL	Download
EPLAN Data Portal 757-244/000-010	URL	Download

CAD data

2D/3D Models 757-244/000-010	URL	Download
------------------------------	-----	----------

Subject to changes. Please also observe the further product documentation!



Environmental Product Compliance

Compliance Search

Environmental Product Compliance 757-244/000-010

URL

Download

M12 sensor/actuator box; 4-way; 4-pole; 10 m

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.