



MATERIAL : FLAME RETARDANT OF ABS ( UL94-V0 )  
 COLOR: BLACK  
 FINISH:  
 SHELL EXTERIOR SURFACES ARE TEXTURED.  
 RECESSED AREAS ON EXTERIOR ARE SMOOTH.  
 FOUR (4) INTERNAL BOSSES ON EACH SHELL ARE  
 DESIGNED TO TRAP PCB BETWEEN ASSEMBLED  
 SHELL HALVES.  
 FOUR (4) #4-24 x .375 LG. SCREWS (BLACK) ARE  
 SUPPLIED FOR ASSEMBLING SHELL HALVES  
 ALL DIMENSIONAL TOLERANCES ARE +/- .015

TOLERANCES:		ITEM REQ'D	PART NO.	DESCRIPTION
±.005 BETWEEN HOLE CENTERS	MAT: NOTED	SCALE:	NAME:	
±.015 FROM SHEARED EDGE	FINISH: BLACK	DR. RD 10-13-08	HAND-HELD BOX STYLE P	
±.032 FROM A BENT SURFACE	CH.		4.53 X 3.27 X 1.26	
±.063 BETWEEN ASSEMBLED SURFACES	APP.		BUD INDUSTRIES, INC.	
UNLESS OTHERWISE SPECIFIED			WILLOUGHBY, OHIO	
QTY. USED ON			DWG. NO. HH-3643	