



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

RPC-1.85 according to	IEC 61169-32
RPC-1.85 mechanically compatible with	RPC-2.40
Waveguide	WR-15
Flange	UG-385/U

Material and plating

Connector parts

Center conductor	Material	CuBe
Outer conductor RPC-1.85		Stainless steel
Waveguide		Brass

Plating

Gold, min. 1.27 µm, over nickel
Passivated
Gold, min. 1.27 µm, over nickel

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

FB00035/12.20/6.4

Electrical data

Impedance	50 Ω
Frequency	50 GHz to 70 GHz
Return loss	≥ 18 dB, 50 GHz to 70 GHz
Insertion loss	≤ 0.6 dB, 50 GHz to 70 GHz

Mechanical data

Mating cycles RPC-1.85	≥ 500
Maximum torque RPC-1.85	1.70 Nm
Recommended torque RPC-1.85	0.90 Nm
Recommended torque WR15	1.10 Nm
Gauge RPC-1.85	0.00 mm to 0.05 mm

Environmental data

Temperature range	- 40 °C to +85 °C
RoHS	compliant

Packing

Standard	1 pce in box
Weight	19 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

For the installation of the electrotechnical equipment, particular electrotechnical expertise is required.



Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Marcel Panicke	11.02.19	Lars Ramtke	25.06.21	b00	21-1076	Marion Striegler	25.06.21

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de	Tel. : +49 8684 18-0 Email : info@rosenberger.de	Page 2 / 2
--	---	---------------