

## Hose holder with cover - WP-BASE C PA HF 28,2 BK - 3240962

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Hose holder with cover

Image shows WP-TCC PA HF 10.0 BK version

### Key Commercial Data

Packing unit	1 STK
Minimum order quantity	25 STK
Weight per Piece (excluding packing)	12.0 g
Custom tariff number	39174000
Country of origin	Germany

### Technical data

#### Dimensions

Hole diameter	6.5 mm
Diameter	28.5 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 115 °C
---------------------------------	-------------------

#### General

Color	black
Components	Halogen-free
Flammability rating according to UL 94	V0
Material	PA

#### Standards and Regulations

Connection in acc. with standard	UL
Flammability rating according to UL 94	V0

# Hose holder with cover - WP-BASE C PA HF 28,2 BK - 3240962

## Classifications

### eCl@ss

eCl@ss 4.0	27141131
eCl@ss 4.1	27141131
eCl@ss 5.0	27141131
eCl@ss 5.1	27141120
eCl@ss 6.0	27141120
eCl@ss 7.0	27141120
eCl@ss 8.0	27439208

### ETIM

ETIM 3.0	EC000897
ETIM 4.0	EC000127
ETIM 5.0	EC001171

### UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121411

## Approvals

### Approvals

---

Approvals

UL Recognized

---

Ex Approvals

---

Approvals submitted

---

### Approval details

UL Recognized 
---

## Hose holder with cover - WP-BASE C PA HF 28,2 BK - 3240962

### Accessories

#### Accessories

#### Corrugated pipe

Protective hose - WP-PA HF 28,5 BK - 3240684



Polyamide protective hose, inflammability class V0, UV resistant

---

Protective hose - WP-PA HF-HB 28,5 BK - 3240842



Polyamide protective hose, inflammability class HB, UV resistant

---