



### SOT-223



### Pin Definition:

1. Base
2. Collector
3. Emitter

### PRODUCT SUMMARY

$BV_{CBO}$	-560V
$BV_{CEO}$	-560V
$I_C$	-150mA
$V_{CE(SAT)}$	-0.5V @ $I_C=-50mA, I_B=-10mA$

### Features

- Low Saturation Voltages
- High Breakdown Voltage

### Structure

- Epitaxial Planar Type
- PNP Silicon Transistor

### Ordering Information

Part No.	Package	Packing
TSA1765CW RPG	SOT-223	2.5Kpcs / 13" Reel

Note: "G" denotes for Halogen Free

### Absolute Maximum Rating (Ta = 25°C unless otherwise noted)


Parameter	Symbol	Limit	Unit
Collector-Base Voltage	$V_{CBO}$	-560	V
Collector-Emitter Voltage	$V_{CEO}$	-560	V
Emitter-Base Voltage	$V_{EBO}$	-7	V
Collector Current	$I_C$	-150	mA
Collector Current(Pulse)	$I_{CP}$	-500	
Base Current	$I_B$	-50	
Total Power Dissipation @ $T_C=25^\circ C$	$P_{tot}$	2	W
Operating Junction Temperature	$T_J$	+150	°C
Operating Junction and Storage Temperature Range	$T_{STG}$	- 55 to +150	°C

### Electrical Specifications (Ta = 25°C unless otherwise noted)


Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Collector-Base Breakdown Voltage	$I_C = -1mA, I_E = 0$	$BV_{CBO}$	-560	--	--	V
Collector-Emitter Breakdown Voltage	$I_C = -1mA, I_B = 0$	$BV_{CEO}$	-560	--	--	V
Emitter-Base Breakdown Voltage	$I_E = -10\mu A, I_C = 0$	$BV_{EBO}$	-7	--	--	V
Collector Cutoff Current	$V_{CB} = -560V, I_E = 0$	$I_{CBO}$	--	--	-100	nA
Emitter Cutoff Current	$V_{EB} = -7V, I_C = 0$	$I_{EBO}$	--	--	-100	nA
Collector-Emitter Saturation Voltage	$I_C = -20mA, I_B = -2mA$	$V_{CE(SAT) 1}$	--	--	-0.2	V
	$I_C = -50mA, I_B = -10mA$	$V_{CE(SAT) 2}$	--	--	-0.5	
Base-Emitter Saturation Voltage	$I_C = -50mA, I_B = -10mA$	$V_{BE(SAT) 1}$	--	--	-1.0	V
Base-Emitter on Voltage	$V_{CE} = -10V, I_C = -50mA$	$V_{BE(ON)}$	--	--	-1.0	V
DC Current Transfer Ratio	$V_{CE} = -10V, I_C = -1mA$	$h_{FE 1}$	150	--	--	
	$V_{CE} = -10V, I_C = -50mA$	$h_{FE 2}$	80	--	300	
	$V_{CE} = -10V, I_C = -100mA$	$h_{FE 3}$	--	15	--	
Transition Frequency	$V_{CE} = -20V, I_E = -10mA$	$f_T$	50	--	--	MHz
Output Capacitance	$V_{CB} = -20V, f = 1MHz$	$C_{ob}$	--	--	8	pF

**Electrical Characteristics Curve** ( $T_a = 25^\circ\text{C}$ , unless otherwise noted)


**Figure 1. Static Characteristics**




**Figure 2. DC Current Gain**




**Figure 3. VCE(SAT) v.s. VBE(SAT)**




**Figure 4. Power Derating**



**Figure 5. Safety Operation Area**




**SOT-223 Mechanical Drawing**



Unit: Millimeters

**Marking Diagram**



- Y** = Year Code
- M** = Month Code for Halogen Free Product
- O** =Jan    **P** =Feb    **Q** =Mar    **R** =Apr
- S** =May    **T** =Jun    **U** =Jul    **V** =Aug
- W** =Sep    **X** =Oct    **Y** =Nov    **Z** =Dec
- L** = Lot Code

**Not Recommended**

### Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.