


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00026	Connector, dc plug, 5.5x2.5xL23 mm, molding style, spring contacts	1	
2	50-00024	Connector, dc plug, 5.5x2.1xL23 mm, molding style, spring contacts	1	
3	30-00395	Wire, 2C TS, 18 AWG, UL2468, 300V, 80C, 4.4 mm, VW-1, PVC, 87A	1	
4	24-00003	Overmold, PVC	2	black



**Notes:**  
Functionally equivalent components may be substituted

Wiring Diagram		
50-00026	wire color	50-00024
center	black with stripe	center
sleeve	black	sleeve

Revision: A	Date: 01/19/2017	Description: Initial release	Prepared: GL Digitally signed by GL Date: 2018.01.19 08:50:58 -08'00'	Notes: RoHS compliant	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>
			Verified: AW Digitally signed by AW Date: 2018.02.14 09:01:45 -08'00'	Function test: no open, no short circuit, no intermittent	
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 305 mm, 5.5x2.5x12 mm 50-00026 dc plug to 5.5x2.1x12 mm 50-00024 dc plug, 18 AWG, UL2468	Size: A Part number: 10-02543
					Scale: 1:1  Sheet 1 of 1

5

4

3

2

1