

## Coaxial Cable Connector 21\_N-50-4-76/133\_U

### Description

Straight cable jack

Interface standards

IEC 61169-16\_MIL-STD-348A/304\_CECC 22210



### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	11 GHz

#### Mechanical Data

Centre contact	crimped
Outer contact	crimped
Weight	0.0356 kg

#### Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

### Related Documents

Outline drawing	DOU-00006335
Catalogue drawing	DCA-00006337
Assembly instruction	DOC-0000179851

### Ordering Information

Bulk 100 pcs package	21_N-50-4-76/133_UH
----------------------	---------------------

### Additional Information

Suitable cables	S_04172_D, S_04262_D, SX_04172_B-60
-----------------	-------------------------------------