

ITEM	PART#	DESCRIPTION	QTY	UOM
A,B	39014031	3CKT RECEPTACLE HOUSING 555703R2210	2	PC
C	39000077	MiniFit Term Crp Fem Chn Bs Tin 16awg	6	PC
D	--	PAPER PRINTED PAPER WHITE	1	PC

FROM	TO	DESCRIPTION	COLOR
A1	B3	1X16AWG DISC PVC BK UL1015 HOOKUP	BLACK
A2	B2	1X16AWG DISC PVC BK UL1015 HOOKUP	BLACK
A3	B1	1X16AWG DISC PVC BK UL1015 HOOKUP	BLACK




TABLE			
PART NUMBER	L1	L2	TITLE
2153201031	150±8	63 REF	MINIFIT JR SR R-R 3 CIRCUIT 150MM Sn
2153201032	300±10	138 REF	MINIFIT JR SR R-R 3 CIRCUIT 300MM Sn
2153201033	600±10	288 REF	MINIFIT JR SR R-R 3 CIRCUIT 600MM Sn

NOTES

1. Cable assembly must pass 100% continuity and polarity test.
2. Connector view shown is from mating side.
3. Label text must be 2mm max. in height with Arial font.
4. Label must be wrapped in flag type on a single cable.

MOLEX P/N
MOLEX
BATCH WK/YR

DETAIL A

REVISION			
DATE	REV	DESCRIPTION	CHANGER
2020/03/23	A	INITIAL RELEASE	ARAJU

FUNCTIONAL SYMBOLS $\frac{E}{A} = 0$ $\frac{E}{E} = 0$ $\frac{E}{P} = 0$ DIVISIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC:		
	DIMENSION UNITS	SCALE	GENERAL TOLERANCES (UNLESS SPECIFIED)		
	mm	NTS	ANGULAR TOL ± °		
	EC NO: 638380		4 PLACES ±		
DRWN: AS20		3 PLACES ±		2020/04/06	PRODUCT CUSTOMER DRAWING DOCUMENT NUMBER: 2153201031 DOC TYPE: PSD DOC PART: 000 REVISION: A
CHK'D: RDESAI01		2 PLACES ±		2020/05/28	
APPR: RDESAI01		1 PLACE ±		2020/05/28	
INITIAL REVISION:		0 PLACES ±		2020/04/06	MATERIAL NUMBER: SEE TABLE CUSTOMER: GENERAL MARKET SHEET NUMBER: 1 OF 1
DRWN: AS20		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		2020/05/28	
APPR: RDESAI01		THIRD ANGLE PROJECTION	DRAWING	SERIES	
			A4-SIZE	215320	