

Data sheet | Item number: 756-5510/030-010

Sensor/Actuator cable; M8 socket; angled; M12A plug; angled; 3-pole;




Length: 1 m



www.wago.com/756-5510/030-010



 Picture differs from the item.



Item description

Short description:

- PUR, halogen-free
- Suitable for drag chains
- Good resistance to microbes, hydrolysis, oil, chemicals and UV radiation.
- Good chemical resistance.
- Cable used: UL listed

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

Data

Technical data

General

Operating voltage	AC/DC 60 V
Operating current	4 A
Rated surge voltage	1.5 kV
Contact resistance	10 mΩ
Conductor resistance	≤ 60 Ω/km
Pollution degree	3 per VDE 0110
Protection type	IP67
Ambient (operating) temperature (static)	-50 ... +90 °C
Ambient (operating) temperature (dynamic)	-25 ... +90 °C

Suitable for drag chains

Bending radius	10 x cable diameter (min.)
Bending cycles	2 Mio.
Acceleration (min.)	5
Travel speed (max.)	3.33
Travel path (horizontal) max.	5
Travel path (vertical) max.	2
Torsional capacity	180

Cable

Cable length	1 m
Type code	LiF9YH-11YH or LiF9YC11YFHF
Conductor configuration	Bare copper wire, fine-stranded (42 x 0.1 mm)
Conductor insulation	PP9Y (halogen-free)
Sheath material	Polyurethane (PUR), halogen-free per DIN VDE 0472 Part 815, flame resistant per IEC 332-2, self-extinguishing
Sheathed cable color	black
Sheathed cable diameter	3.9 ... 4.3 mm

Connector

Connection type	M8 socket - M12 plug
Cable connection direction to mating direction	90 °
Cable connection direction to mating direction (2)	90 °

Subject to changes. Please also observe the further product documentation!



Connector interface coding (cable/adapter) 2 1	A-coded
Housing material	Polyurethane (PUR)
Contact material	CuSn
Tightening torque	0.6 ... 1 Nm

Commercial data

eCl@ss 10.0	27-06-03-11
eCl@ss 9.0	27-06-03-11
ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	10 (1) pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918975919
Customs tariff number	85444290900

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant, With Exemption
RoHS Exemption	6(c)
SCIP notification number (Austria)	947217cd-4567-4a25-b534-1ff9a3e14585
SCIP notification number (Belgium)	d5300d0a-a4ae-455f-bcdb-a906e617b05d
SCIP notification number (Bulgaria)	1bbd3206-2ec8-435c-b9d4-59ce94431467
SCIP notification number (Czech Republic)	7065146d-e809-400d-a7e6-70623e6141a1
SCIP notification number (Denmark)	9ed18af0-06e9-467f-86c5-49877de1f50c
SCIP notification number (Finland)	ec75db23-935c-4188-bfa4-4fe617ff6226
SCIP notification number (France)	c399335a-d783-4c38-9d14-274f90450486
SCIP notification number (Germany)	198e143e-cf00-4771-a2a5-e4bc6d624565
SCIP notification number (Hungary)	33e53238-a36a-4bf1-91a5-13773dfc5c20
SCIP notification number (Italy)	30c40f4b-b28b-422f-9a61-1512a50dd931
SCIP notification number (Netherlands)	c0a3fc96-e6c9-41d5-8a60-396246af9d4f
SCIP notification number (Poland)	e69274ee-9004-47ce-bc01-9f9a90ff25c0
SCIP notification number (Romania)	8a4460b9-8aaf-4070-b13a-badb11c41be1
SCIP notification number (Sweden)	dc1b44ec-6db2-4e27-9d21-8681255a2db1

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.



Downloads

Documentation

Bid Text

756-5510/030-010 X81 - Datei	2019 Feb 19	xml 3.3 kB	Download
---------------------------------	-------------	---------------	----------

756-5510/030-010 doc - Datei	2017 Sep 20	doc 26.1 kB	Download
---------------------------------	-------------	----------------	----------

System Description

IP67 Cables and Pluggable Connectors		pdf 161.6 kB	Download
--------------------------------------	--	-----------------	----------

CAD/CAE-Data

CAE data

WSCAD Universe 756-5510/030-010		URL	Download
---------------------------------	--	-----	----------

WSCAD Universe 756-5510/030-010		URL	Download
---------------------------------	--	-----	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 756-5510/030-010 Sensor/Actuator cable; M8 socket; angled; M12A plug; angled; 3-pole; Length: 1 m		URL	Download
---	--	-----	----------

Installation Notes

Subject to changes. Please also observe the further product documentation!