



| NO. | MASSE / DIMENSIO |
|-----|------------------|
| A   | 46.7             |
| B   | 24.05            |
| C   | 4                |
| D   | 33.8             |
| E   | 41.4             |
| F   | 39.7             |
| G   | 50.8             |
| H   | M5               |

| NO. | BESCHREIBUNG / DESCRIPTION              |
|-----|---|
| 2   | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 6   | KONTAKTBUCHSE / CONTACT SOCKET          |
| 8   | DOSENGEHÄUSE / SHELL                    |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Specification and Dimensions subject to change  
 Drawings illustrate normal insulator positioning

|                                |   |
|--------------------------------|---|
| <b>Material Specification:</b> |   |
| Shell Material:                | Aluminium alloy                               |
| Shell Plating:                 | Olive drab chromate over cadmium (conductive) |
| Insulator Material:            | CR-Elastomere                                 |
| Contact Material:              | Copper alloy                                  |
| Contact Plating:               | Hard silver                                   |

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for  
**CUSTOMER**

description **CA3102E28-11S-B-109**  
 Box mounting receptacle (rear mount, threaded holes)

**ITT**  
 Engineered for life  
 ITT CANNON GmbH  
 D - 71384 Weinstadt/Germany

AWG Crimp / Socket / Layout: 28-11

© All rights reserved. Reproduction or issue to third in any form  
 whoever is only permitted with written authorization of ITT Cannon

page 1/1  
 revision 1730 14. May 19