

## Conductor marker carrier - PATO 2/12 - 0827082

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Conductor marker carrier, transparent, Unlabeled, Mounting type: Clip on, Cable diameter: 2.8-4.4 mm, Lettering field: 4 x 12 mm

The figure shows a similar product

### Product Features

- Can be labeled using UC-WMT ... and US-WMT ... plastic labels or EMT insert strips
- These marking collars are used for subsequent labeling of systems that have already been wired

### Key commercial data

Packing unit	1 pc
Minimum order quantity	1000 pc
Custom tariff number	39269097
Country of origin	Germany

### Technical data

#### Dimensions

Width (a)	12 mm
-----------	-------

#### Ambient conditions

Ambient temperature (operation)	-50 °C ... 80 °C
---------------------------------	------------------

#### General

Color	transparent
Components	Silicone-free
Inflammability class according to UL 94	V0
Material	PVC

### Classifications

eCl@ss

eCl@ss 4.0	24190208
------------	----------

## Conductor marker carrier - PATO 2/12 - 0827082

### Classifications

#### eCl@ss

eCl@ss 4.1	24190208
eCl@ss 5.0	27149103
eCl@ss 5.1	27400401
eCl@ss 6.0	27400401
eCl@ss 7.0	27400401
eCl@ss 8.0	27400401

#### ETIM

ETIM 2.0	EC000761
ETIM 3.0	EC000761
ETIM 4.0	EC001530
ETIM 5.0	EC001530

#### UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39121410