



Note:
 - Drawings Not To Scale
 - Drawings Subject to Change Without Notice
 - Dimensions are inches next to [Millimeters]

Part No.:

XUB0SNSNL2



Telemecanique
Sensors

Telemecanique Sensors
 1875 Founders Drive
 Dayton, OH 45420-4017
 Customer Care Center : 1-800-435-2121
 Web : www.tesensors.com

Technical Information:

Diffuse with Background Suppression:
 Diffuse: 300.0 mm (11.7 in)
 Polarized Retroreflective: 2000.0 mm (78.7 in)
 Thru Beam: 15000.0 mm (590.6 in)
 Retroreflective:
 Circuit Type: NPN
 Output Mode: Light/Dark Operate
 Power: DC
 Voltage Range: 12-24 VDC
 Max Load: 100 mA
 Max Switching Frequency : 250 Hz
 Temp Range: -25° to 55° C (-13° to 131° F)
 NEMA Type: 4X (indoor use only)
 IP Rating: 67
 Standards: UL, CE Rohs

Specification:

Sensor Type: Multi-Mode
 Description: Photoelectric, Multi-Mode, 18 mm Barrel, 12-24 VDC
 Body Style: Barrel
 Diameter: 18 mm
 Housing Material: Metal - Stainless Steel
 Face Material: PMMA
 Adjustment: Pushbutton teach
 Cable Size: 5.0 m (16.4 ft)
 Connector Type:
 Special Features: