



**SS** Stainless Steel

**Metric table**

Dimensions in: millimeters - inches

1 d <sub>1</sub>	2 d <sub>2</sub> Thread	3 l <sub>1</sub>					l <sub>2</sub>		d <sub>3</sub>		d <sub>4</sub>	h <sub>1</sub>	h <sub>2</sub>
		10	15	20	25	-	MS tip	KU tip	MS tip	KU tip			
25 .98	M 5	.39	.59	.79	.98	-	.5 .02	1 .04	3 .12	3 .12	12 .47	16 .63	8 .31
32 1.26	M 6	.39	.63	.79	.98	30 1.18	1 .04	1.3 .05	4 .16	3.5 .14	14 .55	20 .79	10 .39
40 1.57	M 8	.79	.98	1.18	1.57	50 1.97	1.5 .06	1.6 .06	6 .24	5 .20	18 .71	25 .98	13 .51
50 1.97	M 10	.79	.98	1.18	1.77	55 2.17	2 .08	1.9 .07	8 .31	6.5 .26	22 .87	32 1.26	17 .67

**Specification**

- Star knob DIN 6336  
Plastic  
Technopolymer (Polyamide PA)  
Black, matte finish
- Threaded stud  
Stainless steel  
European Standard No. 1.4567  
(AISI 304 Cu)
- Tip
  - Brass **MS**
  - Plastic (Polyacetal POM) **KU**
- RoHS compliant

**Information**

GN 6336.10 star knobs with stainless steel threaded stud are an excellent choice for corrosion-free applications.

The brass or plastic tip on the stud prevents indentations or other damage from occurring.

see also...

- Hollow Knurled Knobs GN 421.10 (with Brass / Plastic Tip)
- Ergostyle® Wing Screws EN 633.10 (with Plastic Tip)
- Hollow Knurled Knobs GN 7336.5 (with Brass / Plastic Tip)
- Star Knobs GN 6336.10 with Loss Protection GN 111.7

How to order

1 2 3 4  
**GN 6336.10-32-M6-20-KU**

1	Handle diameter d <sub>1</sub>
2	Thread d <sub>2</sub>
3	Length l <sub>1</sub>
4	Tip material