



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Aluminium
- Shell Plating : Nickel
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered with Souriau contacts and Accessories
- Temperature Range : -65°C to +200°C
- Salt Spray : 48 hours
- Mass : 31.07 g ± 10%

| Connector dimension |               |
|---------------------|---------------|
| Dim                 | Nominal       |
| P                   | 3.25±0.2      |
| PP                  | 4.93±0.2      |
| R1                  | 29.36         |
| R2                  | 26.97         |
| S                   | 36.5±0.3      |
| V                   | 20.83+0/-1.25 |
| W                   | 2.1/2.5       |
| Z                   | 31.5 Max      |
| VV THREAD           | M28x1-6g      |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)


|         |                             |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR      | Not Listed                  |

**PN: 8D019F11PB**

|                |                                       |                                |   |
|----------------|---------------------------------------|--------------------------------|---|
| A              | 08-10-2016                            | First Release                  |   |
| ISS            | DATE                                  | Latest modification - by       | MOD N°  |
| Designed By:   |                                       | Date:                          | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | <b>Aluminium Receptacle 8D series</b> |                                |   |
| SCALE          | NA                                    | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b>   |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                |                                | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>A3</b>                             |                                | <b>SOURIAU DRG N° 8D019F11PB-C</b>  |
|                |                                       |                                | SHEET<br>1/2  |

|                |                          |   |   |    |   |    |   |   |                                 |
|----------------|--------------------------|---|---|----|---|----|---|---|---------------------------------|
| BASIC SERIES:  | 8D                       | 0 | - | 19 | F | 11 | P | B | ORIENTATION : B                 |
| SHELL TYPE :   | Square Flange Receptacle |   |   |    |   |    |   |   | CONTACT TYPE : PIN(500 Matings) |
| CONTACT TYPE : | Standard Crimp Contact   |   |   |    |   |    |   |   | CONTACT LAYOUT : 19-11          |
| SHELL SIZE :   | 19                       |   |   |    |   |    |   |   |                                 |
| PLATING :      | F = Nickel               |   |   |    |   |    |   |   |                                 |

Contact Layout



| Contacts<br>(insert arrangement 19-11) |             |             |                     |             |             |
|--|-------------|-------------|---------------------|-------------|-------------|
| Contact position ID                    | Location    |             | Contact position ID | Location    |             |
|  | X-axis (mm) | Y-axis (mm) |                     | X-axis (mm) | Y-axis (mm) |
| A                                      | +105 (2.67) | +260 (6.60) | G                   | -275 (6.99) | -053 (1.35) |
| B                                      | +250 (6.35) | +132 (3.35) | H                   | -250 (6.35) | +132 (3.35) |
| C                                      | +275 (6.99) | -053 (1.35) | J                   | -105 (2.67) | +260 (6.60) |
| D                                      | +179 (4.55) | -215 (5.46) | K                   | +000 (0.00) | +105 (2.67) |
| E                                      | +000 (0.00) | -281 (7.14) | L                   | +000 (0.00) | -092 (2.34) |
| F                                      | -179 (4.55) | -215 (5.46) |                     |             |             |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 19         | -11             | 11                 | 16            | II             | All              | MS20054-11 |

Panel Cutout



| Dim | Nominal    |
|-----|------------|
| ØA  | 32.96 min  |
| ØAA | 28.98 min  |
| R1  | 29.36      |
| ØT  | 3.25 ±0.13 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D019F11PB

|                |                                    |                                |   |
|----------------|------------------------------------|--------------------------------|---|
| A              | 08-10-2016                         | First Release                  |   |
| ISS            | DATE                               | Latest modification - by       | MOD N°  |
| Designed By:   |                                    | Date:                          | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | Aluminium Receptacle 8D series     |                                |   |
| SCALE          |                                    | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b>   |
| NA             |                                    |                                |   |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>             |                                | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D019F11PB-C</b> |                                | SHEET<br>2/2  |