



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 53.4              |
| B   | 1 5/8-18NEF-2A    |
| C   | 39.4              |

| NO. | BESCHREIBUNG / DESCRIPTION              |
|-----|---|
| 2   | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 6   | KONTAKTBUCHSE / CONTACT SOCKET          |
| 7   | ZYLINDERGHÄUSE / BARREL                 |
| 9   | ÜBERWURFMUTTER / COUPLING NUT           |
| 10  | DICHTRING FRONT / FRONT SEALING RING    |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Specification and Dimensions subject to change  
 Drawings illustrate normal insulator positioning

|                                |   |
|--------------------------------|---|
| <b>Material Specification:</b> |   |
| Shell Material:                | Aluminium alloy                               |
| Shell Plating:                 | Olive drab chromate over cadmium (conductive) |
| Insulator Material:            | CR-Elastomere                                 |
| Contact Material:              | Copper alloy                                  |
| Contact Plating:               | Hard silver                                   |

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for  
 CUSTOMER



description CA3106E28-21S-B-F42  
 Plug, straight  
 without Endbell and grommet  
 Solder Cup / Socket / Layout: 28-21

© All rights reserved. Reproduction or issue to third in any form  
 whatever is only permitted with written authorization of ITT Cannon



page 1/1  
 revision 2137 28. Apr 21