



Suitable for bench or 2U rack mounting, the Z+ is a very compact programmable power supply offering power levels from 200 to 800W, voltages from 160 to 650V and currents of up to 5A. Multiple remote programming methods are available including built-in USB, RS232 & RS485 and optional LAN, GPIB & isolated analogue interfaces. The units can operate in either constant current or constant voltage mode and accept a wide 85-265Vac input. The product is backed with a five year warranty.

| Features | Benefits |
|--|--|
| • 2U high | • Low Profile |
| • Built-in USB, RS-232 & RS-485 Interface | • No Additional Cost |
| • Optional LAN, GPIB & Isolated Analog Programming | • Programmable Remote Operation |
| • Bench or Rack Mount | • Flexible Mounting |
| • Constant Current or Voltage Modes | • Seamless Transition (Auto Crossover) |
| • Five Year Warranty | • Low Cost of Ownership |

| Model Selector | | | | | | | | |
|----------------|--------------------------|--------------------------|---------------|----------------------------|-----------------------------|------------------------------------|---------------------------|-----------------------------------|
| Model | Voltage Adjust Range (V) | Current Adjust Range (A) | Max Power (W) | Ripple (RMS) 5Hz-1MHz (mV) | Noise Voltage 20MHz BW (mV) | Ripple Current (RMS) 5Hz-1MHz (mA) | Efficiency (100-200VAC) % | Front Panel Output Jacks (Option) |
| Z160-1.3-U | 0 - 160 | 0 - 1.3 | 208 | 10 | 100 | 1.2 | 79 / 81 | Yes |
| Z160-2.6-U | 0 - 160 | 0 - 2.6 | 416 | 10 | 100 | 1.5 | 84 / 86 | Yes |
| Z160-4-U | 0 - 160 | 0 - 4 | 640 | 10 | 100 | 2 | 86.5 / 88.5 | Yes |
| Z160-5-U | 0 - 160 | 0 - 5 | 800 | 10 | 100 | 2 | 86.5 / 88.5 | Yes |
| Z320-0.65-U | 0 - 320 | 0 - 0.65 | 208 | 25 | 150 | 0.8 | 79 / 81 | Yes |
| Z320-1.3-U | 0 - 320 | 0 - 1.3 | 416 | 25 | 150 | 1 | 84 / 86 | Yes |
| Z320-2-U | 0 - 320 | 0 - 2 | 640 | 30 | 150 | 1.5 | 87 / 88.5 | Yes |
| Z320-2.5-U | 0 - 320 | 0 - 2.5 | 800 | 30 | 150 | 1.5 | 86.5 / 89 | Yes |
| Z375-2.2-U | 0 - 375 | 0 - 2.2 | 825 | 30 | 150 | 1.5 | 87.5 / 89.5 | Yes |
| Z650-0.32-U | 0 - 650 | 0 - 0.32 | 208 | 60 | 150 | 0.5 | 79 / 81 | Yes |
| Z650-0.64-U | 0 - 650 | 0 - 0.64 | 416 | 60 | 150 | 0.6 | 84 / 86 | Yes |
| Z650-1-U | 0 - 650 | 0 - 1 | 650 | 60 | 250 | 1 | 86.5 / 88.5 | Yes |
| Z650-1.25-U | 0 - 650 | 0 - 1.25 | 812 | 60 | 250 | 1 | 87 / 89 | Yes |

Part Number Example

| | | | | | | | | |
|---------------------------|----------------|--|---|--------------|--|------------|--|----------|
| Z160 | - | 1.3 | - | LAN | - | L2 | - | U |
| Series and output voltage | Output current | blank IEEE IS510 IS420 LAN | USB, RS-232/RS-485 (All models) GPIB Interface* Voltage Programming Isolated Analog Interface* Current Programming Isolated Analog Interface* LAN Interface (Complies with "LXI" Class C) | blank -L2 | No front output jacks Output (insulated) jacks* | U blank | North America AC cord No AC Cord | |
| | | | | Preferred | | | Other countries upon request (special order) | |

* Requires wide body case (105mm wide)

| Related Products | | |
|---------------------------------|--------------------------------|--|
| Type | Part Number | Description |
| Z+ Low Voltage Series Datasheet | Z+ Low Voltage | Z+ 10V to 100V Programmable Power Supplies |
| 19" Rack Housing | Z-NL100 | Accepts four 105mm width units or six 70mm width units |
| Dual/Triple Housing | Z-NL200 | Accepts two 105mm case units or three 70mm case units |
| Blanking Panel | Z-BP | 70mm Blanking Panel For 19" Rack |
| Blanking Panel | Z-WBP | 105mm Blanking Panel For 19" Rack |
| Cable | Z-RJ45 | Serial Link Cable (One is included with each power supply) |
| DB9 Cable | Z-485-9 | Communication Cable RS-485 |
| DB9 Cable | Z-232-9 | Communication Cable RS-232 |
| Cable | Z-U | 2m North American AC cord (Included with U option) |

| Specifications | | | | |
|--|--------|--|------------------------------|------|
| Model | | Z160 | Z320 | Z650 |
| Input | | | | |
| Input Voltage Range | Vac | 85 - 265 | | |
| Input Frequency | Hz | 47 - 63 | | |
| Input Current (100/200Vac) | A | 200W: 2.76 / 1.37, 400W: 5.25 / 2.57, 600W: 10 / 4.9, 800W: 10.3 / 5.1 | | |
| Inrush Current at 200Vac (typ) (Cold Start) | A | 200W: <30, 400W: <25, 600W: <25, 800W: <30 | | |
| Leakage Current (220Vac) | mA | <1.2 | | |
| Power Factor (100/200Vac) | - | >0.99 / 0.98 | | |
| Harmonic Compliance | - | Meets IEC61000-3-2 Class A | | |
| Hold Up Time (typ) | ms | 200W: 15, 400W: 15, 600W: 15, 800W: 10 | | |
| Efficiency | - | See Model Selector Table | | |
| Conducted & Radiated EMI | - | IEC/EN61326-1, -B radiated, -A conducted, designed to meet EN55032/EN55024 | | |
| Immunity | - | See IEC61000 reports on website | | |
| Insulation Class | - | Class I | | |
| Safety Certifications and Markings | - | IEC/UL/CSA/EN61010-1,60950, CE Mark and UKCA Mark | | |
| Output | | | | |
| Output Voltage and Current Adjustment | - | See Model Selector Table | | |
| Load Regulation (CV Mode) | % | 0.01 of rated voltage over 0 - 100% load change | | |
| Line Regulation (CV Mode) | % | 0.01 of rated voltage over a 85 - 132 or 170 - 265Vac line change | | |
| Transient Response Recovery Time ⁽¹⁾ | ms | 2 | | |
| Load Regulation (CC Mode) | % | 0.09 of rated current over 0 - 100% Vout change | 0.15 of rated output current | |
| Line Regulation (CC Mode) | % | 0.02 of rated current over a 85 - 132 or 170 - 265Vac line change | | |
| Ripple & Noise (CC or CV Mode) | - | See Model Selector Table | | |
| Temperature Coefficient (CV Mode) | ppm/°C | 30 (following 30 minute warm up) | | |
| Temperature Stability (CV Mode) | % | 0.02 of rated voltage over 8 hours following 30 minute warm up time | | |
| Warm-up Drift (CV Mode) | % | <0.05 of rated output voltage (after 30 min warm up period) | | |
| Temperature Coefficient (CC Mode) | ppm/°C | 100 (following 30 minute warm up) | | |
| Temperature Stability (CC Mode) | % | 0.05 of rated current over 8 hours following 30 minute warm up time | | |
| Load Regulation Thermal Drift (CC Mode) | % | < 0.05 of rated current over 30 minutes after load change | | |
| Warm-up Drift (CC Mode) | % | ±0.1 of rated output current over 30 minutes following power on | | |
| Up Programming Resp Time (CV Mode) (10-90% or 90-10% of Vmax) ⁽²⁾ | ms | 110 | 170 | 170 |
| Down Programming Resp Time (CV Mode) Full Load (10-90% or 90-10% of Vmax) ⁽²⁾ | ms | 180 | 270 | 270 |
| Minimum Load | - | No minimum load required | | |
| Overcurrent Protection | - | User programmable, can be set to foldback mode | | |
| Overvoltage Protection | V | Shut down. User programmable | | |
| Overtemperature Protection | - | User selectable - latched or non-latching | | |
| Remote Sense Compensation (per wire) | V | 5 | | |
| Remote On/Off | - | By applied voltage or dry contact relay (user selectable logic) | | |
| DC Good | - | Open Collector, Low on fail | | |
| Communication | - | RS232, RS485 & USB standard, IEEE488 (GPIB) & LAN optional | | |
| Indicators | - | Green LEDs: FINE, MENU, PREV, PROT, REM, OUTPUT, CV, CC Red LED: PROT (OVP, UVP, OTP, FOLD, AC FAIL). | | |
| Display | - | 4 digits. Accuracy 0.5% of rated voltage or current ±1 count | | |
| Parallel Operation | - | Up to 6 units | | |

| Specifications | | | | |
|----------------------------------|-----------|--|------|------|
| Model | | Z160 | Z320 | Z650 |
| Environmental | | | | |
| Operating Temperature | °C | 0 - 50, full load | | |
| Storage Temperature | °C | -20 to +85 | | |
| Humidity (Non condensing) | %RH | 20 - 90 operating, 10 - 95 storage | | |
| Cooling | - | Internal fan | | |
| Altitude | m | 3000. Derate ambient temperature above 2000. | | |
| Withstand Voltage (For 1 minute) | Vac / Vdc | Input to Ground 2kVac, Input to Output 3kVac, Output to Ground 1380Vdc | | |
| Isolation Resistance | MΩ | >100 at 25°C, 70%RH & 500Vdc | | |
| Vibration (Non operating) | - | IEC60068-2-64 | | |
| Shock (Unpacked) | - | IEC60068-2-27: 20G half sine wave, for a duration of 11ms | | |

| Specifications | | | | | |
|-------------------------|--------|---|--------|--------------------------------------|--------|
| Model | | 200W | 400W | 600W | 800W |
| Other | | | | | |
| Weight (Typ) | g | Standard body 1,900; Wide Body 2,400 | | Standard body 2,100; Wide Body 2,600 | |
| Size (WxHxD) | mm | Standard body: 70 x 83 x 350; Wide Body 105 x 83 x 350 | | | |
| Size (WxHxD) | Inches | Standard body: 2.76 x 3.27 x 13.78; Wide Body 4.13 x 3.27 x 13.78 | | | |
| Connectors | | See outline drawings | | | |
| Case Material | - | Metal case, plastic front panel | | | |
| MTBF - MIL HDBK-217F(3) | Hours | 75,839 | 75,667 | 76,274 | 76,274 |
| Warranty | Years | 5 | | | |

Notes


See website for detailed specifications, test methods and installation manual

(1) Recovery to within 0.5% of rated voltage after a load change of 10-90% (Output current 10-100% of I_{max})


(2) [200W models](#). See [specification on website for 400, 600 & 800W models](#)

(3) Ground, Fixed. Excludes fan. See reliability data on website

Z+ Outline Drawing (70mm wide)



Z+ Outline Drawing (105mm wide) with Optional IEEE, Isolated Analog Interface





TDK-Lambda France SAS

Tel: +33 1 60 12 71 65
france@fr.tdk-lambda.com
www.emea.lambda.tdk.com/fr



Italy Sales Office

Tel: +39 02 61 29 38 63
info.italia@it.tdk-lambda.com
www.emea.lambda.tdk.com/it



Netherlands

info@nl.tdk-lambda.com
www.emea.lambda.tdk.com/nl



TDK-Lambda Germany GmbH

Tel: +49 7841 666 0
info@de.tdk-lambda.com
www.emea.lambda.tdk.com/de



Austria Sales Office

Tel: +43 2256 655 84
info@at.tdk-lambda.com
www.emea.lambda.tdk.com/at



Switzerland Sales Office

Tel: +41 44 850 53 53
info@ch.tdk-lambda.com
www.emea.lambda.tdk.com/ch



Nordic Sales Office

Tel: +45 8853 8086
info@dk.tdk-lambda.com
www.emea.lambda.tdk.com/dk



TDK-Lambda UK Ltd.

Tel: +44 (0) 12 71 85 66 66
info@uk.tdk-lambda.com
www.emea.lambda.tdk.com/uk



TDK-Lambda Ltd.

Tel: +9 723 902 4333
info@tdk-lambda.co.il
emea.lambda.tdk.com/il-en



TDK-Lambda Americas

Tel: +1 800-LAMBDA-4 or 1-800-526-2324
tla.powersolutions@tdk.com
www.us.lambda.tdk.com



TDK Electronics do Brasil Ltda

Tel: +55 11 3289-9599
sales.br@tdk-electronics.tdk.com
www.tdk-electronics.tdk.com/en



TDK-Lambda Corporation

Tel: +81-3-6778-1113
www.jp.lambda.tdk.com



TDK-Lambda (China) Electronics Co. Ltd.

Tel: +86 21 6485-0777
tlc.powersolutions@tdk.com
www.lambda.tdk.com.cn



TDK-Lambda Singapore Pte Ltd.

Tel: +65 6251 7211
tts.marketing@tdk.com
www.sg.lambda.tdk.com



TDK India Private Limited, Power Supply Division

Tel: +91 80 4039-0660
mathew.philip@tdk.com
www.sg.lambda.tdk.com

