

## 28177.7 PVC-TAA 15X44 K WH

Device and installation marker, Length: 44 mm, Width: 15 mm, Colour: White

RAL: 9010

### Business data

Article number	28177.7
Article name	PVC-TAA 15X44 K WH
GTIN (EAN)	4044211213268
Packaging unit	120
Quantity unit	PC
Number of markers per card	12 ST
Weight per piece (not including packaging)	1.54 g
Weight per piece (including packaging)	1.54 g
Unit of weight	G
Customs number	39199080
Country of origin	IT
Prio-Article	28177.7
Product description	Device and installation marker

## 28177.7 PVC-TAA 15X44 K WH

---

### Technical data

---

#### Dimensions

Length	44 mm
Width	15 mm

#### Materials

Marker material	PVC
Flammability class UL 94	V-0
Working temperature, min.	-30 °C
Working temperature, max.	60 °C
Processing temperature, min.	10 °C
Processing temperature, max.	40 °C
Silicone-free	✓

#### Further technical data

Mounting	Self-adhesive
Software code	854

#### Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2022-06-10
REACH Candidate Substance Note	No
RoHS Conform	yes

---

### Media

---

### Accessories

#### Printer



Thermal transfer printer TTPCard including a power cord, USB cable, dust cover, black thermal transfer film (28010.4), three inlays: CCI-PC-SB 5x5 (28020.0), CCI-PC-CPM-10/BSTR (28027.0), CCI-PC/PVC/PVCF (28041.0), CONTASign PRO software in 16 languages (German, English, French, Italian, Dutch, Spanish, Portuguese, Czech, Polish, Bulgarian, Romanian, Slovenian, Turkish, Chinese, Japanese, Russian) for Windows versions 7, 8, 10. (available for download)

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28000.0</u>	TTPCard Set	4044211207397	1 ST

#### Inlays

Printer inlay

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28041.0</u>	CCI-PC/PVC/PVCF	4044211208097	1 ST