

## Specification Sheet

Part Number: T50SL7.NN6P



Two piece assembly allows the mount to slide along the strap ensuring proper orientation.

Arrowhead style mount provides low insertion and high extraction force.

Arrowhead disc protects against dirt and other impurities.

1-Pc Cable Tie/Arrowhead Mount w/Wings, 6.5"L, 50lb, 0.27 - 0.28" Hole Dia, PA66, Natural, 500/bag

Article Number 111-85479

Type T50SL7

Color Natural (NA)

Quantity Per bag

Product Description  
Wing design helps stabilize the tie in high vibration applications. One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.

Short Description  
1-Pc Cable Tie/Arrowhead Mount w/Wings, 6.5"L, 50lb, 0.27 - 0.28" Hole Dia, PA66, Natural, 500/bag

Global Part Name T50SL7-PA66-NA

Minimum Tensile Strength (Imperial) 50.0

Minimum Tensile Strength (Metric) 225

Length L (Imperial) 6.5

Length L (Metric) 165

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.18

Width W (Metric) 4.6

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Min (Metric) 1.5

Bundle Diameter Max (Imperial) 1.3

Bundle Diameter Max (Metric) 34.0

|   |              |
|---|--------------|
| Thickness T (Imperial)                  | 0.05         |
| Thickness T (Metric)                    | 1.2          |
| Height H (Imperial)                     | 0.4          |
| Height H (Metric)                       | 10.0         |
| Panel Thickness Min (Imperial)          | 0.031        |
| Panel Thickness Max (Imperial)          | 0.098        |
| Panel Thickness Min (Metric)            | 0.8          |
| Panel Thickness Max (Metric)            | 2.5          |
| Mounting Hole Diameter D (Imperial)     | 0.27 - 0.28  |
| Mounting Hole Diameter D (Metric)       | 6.9 - 7.1 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.27         |
| Mounting Hole Diameter D Max (Imperial) | 0.28         |
| Mounting Hole Diameter D Max (Metric)   | 7.1          |
| Disc Diameter (Imperial)                | 0.73         |

Material Polyamide 6.6 (PA66)

|                              |                                  |
|------------------------------|----------------------------------|
| Material Shortcut            | PA66                             |
| Flammability                 | UL 94 V-2                        |
| UV Resistant (Yes/No)        | No                               |
| Operating Temperature        | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33) | Yes                              |
| ROHS Compliant               | Yes                              |
| Package Quantity (Imperial)  | 500                              |
| Package Quantity (Metric)    | 500                              |
| Customs Number               | 3926909988                       |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)