



P1	
1	SILVER
2	RED
3	BLACK
4	WHITE
5	BLUE

WIRING DIAGRAM

- NOTES:
1. MATERIAL: SEE TABLE
  2. FINISHES: SEE TABLE
  3. PACKAGING: PART IS PACKED UNASSEMBLED IN POLY BAG ALONG WITH INSTRUCTION SHEET
  4. LABELING: BARCODE LABEL IS ATTACHED TO OUTSIDE OF POLY BAG
  5. MATES WITH: 5/C FEMALE RECEPTACLE
  6. ELECTRICAL SPECIFICATIONS:  
VOLTAGE RATING: 600V AC/DC  
CURRENT RATING: 8 AMPS

ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH
7	1	O-RING	NITRILE	BLACK
6	1	COMPRESSION NUT	POLYAMIDE PAG	BLACK
5	1	GROMMET	NEOPRENE	BLACK
4	5	CONTACT PIN	Cu ALLOY	GOLD PLATED
3	1	COUPLER	BRASS	NICKEL PLATED
2	1	PIN INSERT	POLYURETHANE	BLACK
1	1	CONNECTOR BODY	POLYAMIDE PAG	BLACK

RELEASED  
EC NO: WNA2010-0417  
DRAWN BY: DR.WHSTONE 2010/01/21  
CHKD BY: WOODMAN 2010/01/22  
APPR: JF MURPHY 2010/01/25

QUALITY SYMBOLS  
▽=0  
▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± .---	± .---
3 PLACES	± .---	± .---
2 PLACES	± .---	± .010
1 PLACE	± 0.3	± .---

ANGULAR ±1/2°

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: IN/MM

DRAWN BY: R. STONE DATE: 2010/01/12

CHECKED BY: B. WOODMAN DATE: 2010/01/15

APPROVED BY: JF MURPHY DATE: 2010/01/22

MATERIAL NO. 848569102

SCALE: 1:1

DESIGN UNITS: INCH

THIRD ANGLE PROJECTION

MINI CHANGE CONNECTOR FIELD ATTACHABLE 5/C, MALE

MOLEX INCORPORATED

DOCUMENT NO. SD-84856-009

SHEET NO. 1 OF 1

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION