ב בר			0	Ξ	A	
4						
			LAYOUT SHOW	N AS EXAMPLE		
	Keying Shown as example					
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal	_				
-Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy	ØS 35.7 Max Z 31 Max VV THREAD M25x1-6g		due to a use of the Prod the Specifications issued by e	for any non-conformity or d ucts which does not comply v ither of the Parties or by a th nendation, technical notice.)	vith ird party	
-Seals & Grommet : Silicon Elastomer			[		& Control List	
<ul> <li>Contact Plating : Gold over copper Alloy 0.8μm minimum</li> <li>Durability : 500 Mating cycles</li> </ul>				FR Not	Listed	:
-Delivered without Souriau contacts			PN: 8D517F08SNL			
-Temperature Range <u>-</u> -65°C to +200°C			I-10-2016 First Release			
-Salt Spray : 48 hours						OD N°
		ISS Designed E	DATE Latest modification - by by: Date:	CUS		
		ті	TITLE Aluminium Plug 8D series			
BASIC SERIES: 8D 5 - 17 F SHELL TYPE : Plug with RFI Shielding	08 S N L Delivered V	SCALE N/O Contacts NA	General Toleran ±	ces:	IPRDS / PROJECT <b>859</b>	
CONTACT TYPE : Standard Crimp Contact	ORI		RIAU WWW.SOURI	AU.COM	This document is the property or SOURIAU it must not be reproduced or	
SHELL SIZE : 17	CONTACT TYPE : SOCKET(				communicated without permissio	
PLATING : F = Nickel	CONTACT LA	YOUT : 17-08 FORMAT	3000	IAU DRG N°		HEET
				.7F08SNL-C		1/2

r	т	۵	н <b>г</b>	m	D	0	
		Contact Layout					
4	-x (	$ \begin{array}{c}                                     $					
	Cont position A B C C D E F	Contacts           Location           X-axis         Y-axis           X-axis           (mm)         (mm)           +.000 (0.00)         +.236 (5.99)           +.128 (3.25)         +.086 (2.18)           +.230 (5.84)        078 (1.98)           +.094 (2.39)        216 (5.49)          094 (2.39)        216 (5.49)					
ω	Shell Arrangement Nuc size no. co	128 (3.25) +.086 (2.18)					
	L						
						SOURIAU shall not be liab due to a use of the Pro the Specifications issued by (professional reco	oducts w y either o
N						PN: 8D	Count FR 0517
					A 14-10-20 ISS DATE Designed By:	116 First Release Latest modification - by Date:	
					TITLE		Alumir
_ <b>_</b>					NA	-{	ar linear rances: ±
					SOURIA		
					FORMAT A3	SOU 800	RIAU 517F(
l	Н	G	F	E	/ D		
					V		

