



NUMBER OF CIRCUITS "XX"	DIM. "A"	DIM. "B"	DIM. "C"	DIM. "D"	ASSEMBLY MATERIAL NO.	ASSEMBLY MATERIAL NO.
02	43.4 (1.71)	11.11 (.438)	33.34 (1.313)	25.9 (1.02)	386390145	396399002
03	54.5 (2.15)	22.23 (.875)	44.45 (1.750)	37.0 (1.46)	386390146	396399005
04	65.7 (2.59)	33.34 (1.313)	55.56 (2.188)	48.1 (1.90)	386390147	396399008
05	76.8 (3.02)	44.45 (1.750)	66.68 (2.625)	59.2 (2.33)	386390148	396399011
06	87.9 (3.46)	55.56 (2.188)	77.79 (3.063)	70.4 (2.77)	386390149	396399015
07	99.0 (3.90)	66.68 (2.625)	88.90 (3.500)	81.5 (3.21)	386390150	396399023
08	110.1 (4.34)	77.79 (3.063)	100.01 (3.938)	92.6 (3.65)	386390151	396399026
09	121.2 (4.77)	88.90 (3.500)	111.13 (4.375)	103.7 (4.08)	(B)386390152	396399029
10	132.3 (5.21)	100.01 (3.938)	122.24 (4.813)	114.8 (4.52)	(B)386390153	396399031

- NOTES:
1. MATERIAL: SEE TABLE
 2. FINISHES: SEE TABLE
 3. PRODUCT SPECIFICATION: NOT REQUIRED
 4. "XX" REFERS TO THE QUANTITY OF CIRCUITS.
 5. SCREWS SUPPLIED UNASSEMBLED.
 6. ROHS COMPLIANT.

ITEM	QTY.	DESCRIPTION	MATERIAL	DESCRIPTION
3	XX	SCREW #6-32X250 PAN PHLZN/BR/STEEL -50	STEEL	ZN, CLEAR CHROMATE
2	XX	TERM WW EXTRA LONG 6C SN/AG/NI	BRASS	TIN/SILVER/NICKEL
1	1	INSULATOR, SR, PC, MOLDED MTG	PBT	BLACK

REV. & REDRAWN EC NO: ETC2008-0073 DRWN: JENCINAS 2007/10/17 CHKD: JENCINAS 2007/11/05 APPR: JMACNEIL 2007/11/05	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ± --- ± --- 3 PLACES ± --- ± .005 2 PLACES ± 0.13 ± .01 1 PLACE ± 0.3 ± --- ANGULAR ± 2 °	DIMENSION STYLE MM/IN DRAWN BY: R. KEMP DATE: 2005/08/17 CHECKED BY: GR DATE: 2005/08/17 APPROVED BY: GR DATE: 2005/08/17	SCALE: 2:1 DESIGN UNITS: INCH THIRD ANGLE PROJECTION	
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO.: SEE CHART DOCUMENT NO.: SD-38639-008	TITLE: 11.11/.438 SR BTS ASSY NO PADS, 81, SQ. WASHER (637XX-W-50-59-81) MOLEX INCORPORATED SHEET NO.: 1 OF 1	
	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				
	SIZE B				