

EHRH

Waterproof RH Transmitter



The EHRH Relative Humidity Transmitter is a waterproof RH sensing element and package which is ideally suited for monitoring relative humidity in high RH/harsh environment applications or where washdowns are required. The unit is designed for continuous monitoring of relative humidity and temperature and is available in $\pm 2\%$ accuracy.

Both the sensor and electronics are contained in an epoxy-hardened enclosure designed for continuous service. A water-tight membrane filter is installed over the RH sensor for increased protection against high RH, contaminants and washdowns. The unit is designed to withstand 100% saturation.

The sensor incorporates a bulk polymer resistance element. The polymer is impervious to most contaminants and, since it is a bulk resistance device, surface contamination such as dust will not alter the accuracy of the readings.

The unit is provided with continuous temperature compensation which adjusts for temperature-induced change in the RH sensor output. The compensation provides high measurement accuracy over the entire operating range of the instrument.

Features

- Waterproof sensing element and housing
- Compact transmitter with built-in sensor
- Bulk polymer resistance RH sensor
- Resistant to contamination
- Thermistor temperature measurement
- Temperature compensation

Applications

- Greenhouses
- Textile mills
- Food processing
- Shipping containers
- Swimming pools
- Hospital suites

EHRH Specifications

Humidity

Sensing Element

Resistance change of bulk polymer sensor

Accuracy at 77°F (25°C)

±2% RH. 30 to 95% RH including hysteresis, linearity, and repeatability.

Temperature Effect

Less than 0.11% per °F (0.06% per °C)

Sensitivity

0.1% RH

Repeatability

0.5% RH

Linearity

See accuracy

Hysteresis

Less than 1%

Operating Range, Sensor & Electronics

0% to 100% RH, -20°C to 54°C (-4°F to 129°F)

Maximum Air Velocity

10,000 ft/minimum (3,048 m/minimum)

Output Ranges

4 to 20 mA current, two-wire, loop-powered for 0 to 100%, RH (standard) into 0 to 900 Ω

Adjustment

Zero

±20%, non-interactive

Span

±10%, non-interactive

Long Term Stability

Less than 2% drift per year typical

Power Supply

Voltage

12 to 36 VDC

Wiring Connection

Deutsch four-position waterproof connector (For front wiring only_flying leads for back wiring).

Temperature

Sensing Element

Thermistor, 10 KΩ at 77°F (25°C), two-wire measurement

Accuracy at 77°F (25°C)

±0.5°F (±0.3°C). Also available with 100 (RTD with 4 mA to 20 mA analog output.

Consult factory for further information

Part Number Configuration

Order Codes:	[1]-[2]-[3]-[4]
1	Model Designation
	EHRH-2 Relative Humidity and 10K thermister outputs
	EHRHT-2 Relative Humidity and signal conditioned temperature outputs
2	Output(s)
	I Current (4-20mA) EHRH and EHRHT
	V5 Voltage (0-5 VDC) EHRH only
	V10 Voltage (0-10 VDC) EHRH only
3	Wiring
	F Front, with waterproof connector
	B Back, flying leads
4	Temperature Channel Range (EHRHT Only)
	1 -20°F to +140°F Temperature Range (Standard Range)
	2 0°F to +150°F Temperature Range
	3 0°F to 100°F Temperature Range
	4 +32°F to +132°F Temperature Range
	5 +50°F to +130°F Temperature Range
	6 -40°F to +140°F Temperature Range
	7 Custom Temperature Range

Example: EHRH-2-V5-F RH transmitter with 10K thermistor, 2% accurate RH, 0-5 volt RH output and front-wired (waterproof connector).

All units have a standard 3-Point factory calibration (30, 50, 80% RH @ 25°C) standard relative humidity output range is 0 to 100%. Standard temperature output range is -20°F to +140°F. Standard relative humidity and temperature output signal is 4-20 mA.

Amphenol
Advanced Sensors

www.telaire.com
www.amphenol-sensors.com

© 2014 Amphenol Corporation. All Rights Reserved. Specifications are subject to change without notice. Other company names and product names used in this document are the registered trademarks or trademarks of their respective owners.

AAS-920-233D-03/2014