

Housing cover - ME-IO 18,8 C 2U MC18 7035 - 2202581

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




DIN rail housing, 2U for marking lid, Housing cover, width: 18.9 mm, color: light gray (7035)

Your advantages

- Item is from the ME-IO product range
- Tool-free mounting
- Available in overall widths from 18.8 mm
- Inflammability class V0 according to UL 94
- Front push-in connection technology
- Can be mounted on the DIN rail
- Optional with bus connector for DIN rail mounting



Key Commercial Data

Packing unit	30 pc
Minimum order quantity	30 pc
GTIN	 4 055626 146225
GTIN	4055626146225

Technical data

Item properties

Brief article description	Housing cover
Type	ME-IO 18,8 C 2U MC18 7035
Order No.	2202581
Housing type	DIN rail housing
Type	2U for marking lid
Mounting type	Snap in

Dimensions

Width [w]	18.9 mm
-------------	---------

Housing cover - ME-IO 18,8 C 2U MC18 7035 - 2202581

Technical data

Dimensions

Height [h]	21.9 mm
--------------	---------

Material data

Flammability rating according to UL 94	V0
Housing material	Polyamide

PCB data

Mounting position	Vertical (horizontal DIN rail)
-------------------	--------------------------------

Packaging information

Pieces per package	30
Denomination packing units	Pcs.

Standards and regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals


Approvals

UL Recognized / EAC

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 240868
---------------	---	---	---------------

EAC		B.01742
-----	---	---------

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>