



CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
6B D.C. RESISTANCE	1-3 @20°C	0.46 ohms max.
6B D.C. RESISTANCE	6-4 @20°C	0.48 ohms max.
INDUCTANCE	1-3 10kHz, 100mVAC, Ls	1.0mH min.
6G INTERWINDING CAPACITANCE	1-6 100kHz, 10mVAC, Cs	12.5pF typ.
DIELECTRIC	1-6 1875VAC, 1 second	1500VAC, 1 minute
URNS RATIO	(6-4):(1-3)	1.1:1, ±2%



GENERAL SPECIFICATIONS:

- 6B OPERATING TEMPERATURE RANGE: -40°C to +125°C.
- CURRENT RATING: 100mAAC
- VOLTAGE-TIME: 7VuS
- 6D Qualified to AEC-Q200.

Wire insulation & RoHS status not affected by wire color.  
Wire insulation color may vary depending on availability.

REV.	DATE	Packaging Specifications		Tolerances unless otherwise specified:	DRAWING TITLE	PART NO.
6G	4/21	Method: Tape & Reel		Angles: ±1°	<b>TRANSFORMER</b>	<b>760390011</b>
6F	12/20	PKG-0895	Fractions: ±1/64	This drawing is dual dimensioned. Dimensions in brackets are in millimeters.		
6E	7/16	www.we-online.com/midcom				SPECIFICATION SHEET 1 OF 1
6D	3/16	SEE REVISION SHEET FOR REVISION LEVEL				