

3-3/4 digits 3999 Counts Auto Range Digital Multimeter

Item: MT-1217

- Complies with newest CE safety standard
- 3-3/4 digits 3999 counts
- Large and easy to read display panel
- Overload and fuse protection
- Built-in stand

Extra function: Auto range, relative reference, backlight, data hold, auto power off, low battery indication



Specification	
DCV	400mV/4V/40V/400V ±(0.5%+4d), 1000V ±(1.0%+6d)
ACV	4V/40V/400V ±(0.8%+6d), 750V ±(1.0%+10d)
DCA	400µA/4000µA ±(1.0%+10d), 40mA/400mA ±(1.0%+10d), 4A/10A±(1.2%+10d)
ACA	400µA/4000µA ±(1.5%+10d), 40mA/400mA ±(1.5%+10d), 4A±(2.0%+15d) ; 10 A±(2.5%+15d)
Resistance	400Ω ±(0.8%+5d), 4k/40k/400kΩ/4MΩ± (0.8%+4d), 40MΩ ±(1.2%+10d)
Frequency	400/4K/20KHz ±(0.5%+10d)
Capacitance	40nF ±(0.5%+30d), 400nF/4µF/20µF ±(3.5%+8d)
Temperature	(-20°~1000°) < 400°±(1.0%+5d) (-20°~1000°) >= 400°±(1.5%+15d)
Duty Cycle	0.1%~99.9%
Continuity with beeper	Y Diode Test Y
Transistor hFE test	Y (with socket)
Fuse	0.4A/250V Resettable fuse, 10A/250V Fuse
Power source	9Vx1(not included)
Size (HxWxD)mm	7.17" x 3.54" x 1.81"
Individual packing	Color Box

Order Today! SalesSupport@EclipseTools.com

Eclipse Enterprises, Inc. ● Tel: 804.561.2610 ● Fax: 804.561.2642

13302 Chula Road, Amelia Court House, VA 23002 ● EclipseTools.com