

Housing - HC-STA-D25-CLWS-1TTP16-EL-AL - 1424388


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Coupling housings D25, with single locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, straight, height: 52 mm, cable gland: none, support sleeve: no, 1x Pg16, Standard



Key Commercial Data

Packing unit	1 pc
GTIN	 4 0 5 5 6 2 6 3 7 1 2 8 3
GTIN	4055626371283

Technical data

Dimensions

Height	52 mm
Width	30 mm
Length	80 mm

Ambient conditions

Degree of protection (IP)	IP66
	IP67
Ambient temperature (operation)	-40 °C ... 125 °C

General

Note	For contact inserts HC-D25, A16
Size	D25
Housing type	Coupling housings
Color	gray aluminum
Locking type	with single locking latch
No. of cable outlets	1
Cable outlet	straight
Screw connection	none

Housing - HC-STA-D25-CLWS-1TTP16-EL-AL - 1424388

Technical data

General


Type of the screw connection	1x Pg16
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Material lock	PA
Flammability rating according to UL 94	V0 (Interlock)

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Dimensional drawing



Dimensional drawing

Classifications

eCl@ss

eCl@ss 10.0.1	27440202
eCl@ss 11.0	27440202
eCl@ss 5.1	27261200
eCl@ss 6.0	27261200
eCl@ss 7.0	27440202
eCl@ss 9.0	27440202

ETIM

ETIM 6.0	EC000437
ETIM 7.0	EC000437

Approvals

Approvals

Housing - HC-STA-D25-CLWS-1TTP16-EL-AL - 1424388

Approvals

Approvals

UL Recognized / cUL Recognized / DNV GL / EAC / cULus Recognized

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E255026
cUL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E255026
DNV GL		https://approvalfinder.dnvgl.com/	TAE000037S
EAC			RU C- DE.BL08.B.00511
cULus Recognized			

Accessories

Accessories

Corrugated pipe screw connection

Screw connection - WP-G HF IP66 PG16 BK - 3240891



Cable gland, Pg thread, IP66 protection, straight

Housing - HC-STA-D25-CLWS-1TTP16-EL-AL - 1424388

Accessories

Screw connection - WP-G HF IP69K PG16 BK - 3240877



Cable gland, Pg thread, IP68/69k protection, straight

Screw connection - WP-GA HF IP66 PG16 BK - 3240919



Cable gland, Pg thread, IP66 protection, angled

Screw connection - WP-GA HF IP69K PG16 BK - 3240905



Cable gland, Pg thread, IP68/69k protection, angled

Screw connection - WP-GR HF IP66 PG16 BK - 3240947



Cable gland, Pg thread, IP66 protection, with strain relief

Screw connection - WP-GR HF IP69K PG16 BK - 3240933



Cable gland, Pg thread, IP68/69k protection, with strain relief

Housing - HC-STA-D25-CLWS-1TTP16-EL-AL - 1424388

Accessories

Screw connection - WP-G PP HF PG16 - 3240991



Cable gland made from PP with Pg thread, IP65 protection

Screw connection - WP-GT PP HF PG16 - 3241005



Cable gland made from PP with Pg thread, rotatable, IP54 protection

Screw connection - WP-G BRASS IP40 PG16 - 3241040



Cable gland made from brass with Pg thread, IP40 protection

Screw connection - WP-GT BRASS PG16 - 3241026



Cable gland made from brass with Pg thread, rotatable, IP40 protection

Screw connection - WP-G BRASS IP65 PG16 - 3241054



Cable gland made from brass with Pg thread, IP65 protection

Full screw connection

Housing - HC-STA-D25-CLWS-1TTP16-EL-AL - 1424388

Accessories

Cable gland - G-INS-PG16-S68N-NNES-S - 1411174



Cable gland, cable gland material: Nickel-plated brass, external cable diameter 10 mm ... 14 mm, shielding: no, connecting thread: Pg16, color: silver, with O-ring

Cable gland - G-INSEC-PG16-S68N-NNES-S - 1411199



Cable gland, cable gland material: Nickel-plated brass, external cable diameter 10 mm ... 14 mm, shielding: yes, connecting thread: Pg16, color: silver, with O-ring

Phoenix Contact 2021 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>