



### Main

Range	Thalassa
Product name	Thalassa PLS
Device short name	PLS
Enclosure type	Multi-purpose
Category	Insulating modular rear
Nominal height	7.09 in (180 mm)
Nominal width	10.63 in (270 mm)
Nominal depth	5.31 in (135 mm)
Enclosure mounting	Wall mounted
Device composition	1 rear part on enclosure
Body type	One piece moulded
Type of front cover	Without

### Complementary

Material	Polyester reinforced with fibreglass
Color	Body Gray RAL 7035)
Standards	NEMA classification 13 IEC 62208 NEMA 4X
Product Certifications	UL

### Environment

Electrical Insulation Class	Class II
IP degree of protection	IP66 IEC 60529
IK degree of protection	IK09 IEC 62262
Fire resistance	1760 °F (960 °C) IEC 62208
Ambient Air Temperature for Storage	-22...158 °F (-30...70 °C)

### Ordering and shipping details

Category	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	3606480773976
Nbr. of units in pkg.	1
Package weight(Lbs)	31.39 oz (890.0 g)
Returnability	No
Country of origin	ES

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.91 in (15 cm)
Package 1 width	7.87 in (20 cm)
Package 1 Length	11.42 in (29 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	56
Package 2 Weight	114.29 lb(US) (51.84 kg)
Package 2 Height	39.57 in (100.5 cm)

Package 2 width	21.85 in (55.5 cm)
Package 2 Length	28.74 in (73 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>