

## Universal Reversible USB 2.0 Cable (Reversible A to 5Pin Mini B M/M), 6-in. (15.24 cm)

MODEL NUMBER: UR030-06N



Universal / Reversible "A" connector allows plugging in any direction

### Features

- Universal / Reversible "A" connector plugs in any direction
- Meets or Exceeds USB 2.0 Specifications
- Connects to Cameras, Cell Phones, PDA's, etc with 5-Pin Mini-B USB connectors
- Supports faster data transfer rate (1.5 to 480 Mbps) for low speed and high speed devices including multimedia applications
- Premium double-shielded cables with tinned copper braid and aluminum Mylar foil
- Nickel plated connectors and gold plated copper contacts for superior conductivity.
- Molded connectors and integral strain relief for extra durability and long life.

## Specifications

| OVERVIEW           |                      |
|--------------------|----------------------|
| UPC Code           | 037332182098         |
| Technology         | USB 2.0 (High Speed) |
| USB Cable Type     | Passive              |
| PHYSICAL           |                      |
| Cable Jacket Color | Black                |
| Cable Length (ft.) | 0.5                  |
| Cable Length (m)   | 0.15                 |
| Cable Length (in.) | 6                    |

### Highlights

- Universal / Reversible A connector eliminates guess-work as to connector orientation
- Meets or Exceeds USB 2.0 Specifications
- Connects to Cameras, PDA's, etc with Mini-B 5-Pin connectors

### System Requirements

- Any USB device requiring a USB cable with Mini-B 5-Pin connector
- USB2.0 performance only when used with USB2.0 device and USB2.0 controller

### Package Includes

- 6-in. USB2.0 Universal / Reversible A to Mini-B Device Cable (A Male to 5Pin Mini-B Male)

|                                     |                              |
|-------------------------------------|------------------------------|
| Cable Length (cm)                   | 15.24                        |
| Shipping Dimensions (hwd / in.)     | 0.25 x 0.25 x 6.00           |
| Shipping Dimensions (hwd / cm)      | 0.64 x 0.64 x 15.24          |
| Shipping Weight (lbs.)              | 0.05                         |
| Shipping Weight (kg)                | 0.02                         |
| <b>ENVIRONMENTAL</b>                |                              |
| Operating Temperature Range         | 14 to 122 F (-10 to 50 C)    |
| Storage Temperature Range           | 5 to 140 F (-15 to 60 C)     |
| Operating Humidity Range            | 0% to 90% RH, Non-Condensing |
| Storage Humidity Range              | 0% to 90% RH, Non-Condensing |
| <b>CONNECTIONS</b>                  |                              |
| Side A - Connector 1                | REVERSIBLE USB A (MALE)      |
| Side B - Connector 1                | USB MINI-B 5-PIN (MALE)      |
| <b>WARRANTY &amp; SUPPORT</b>       |                              |
| Product Warranty Period (Worldwide) | Lifetime limited warranty    |