



Notes:

Detailed Product Description:

- 1. Waterproof connector rating is IP67/IP68
- 2. Protected from dust and water during immersion, resistant to many oils and chemical etc.

Other Specification:

- 3. Rating voltage: 60V AC/DC
- 4. Rating current: 3A
- 5. Insulation resistance: >100MΩ.
- 6. Contact resistance of connector: ≤10mΩ.
- 7. Operating Temperature: -25°C ~ +85°C.

WIRE LIST

P1	COLOR	P2
1	BROWN	OPEN
2	WHITE	
3	BLUE	
4	BLACK	

ITEM	SPECIFICATION	Q'TY	UNIT
④	HD PE	3	G
③	BLACK PUR	6	G
②	M8 A CODING 4P/M CONNECTOR	1	SET
①	UL20549 24AWG*4C JACKET BLACK PUR OD=5.0mm	1	PCS

RoHS compliant
Unit: mm

Scale	Free					Date	Name	Customer-No.
TOLERANCE						Drawn	21.11.2018	Segal
.X	±0.5					Approved	26.01.2019	Amy
.XX	±0.20							
DIM	TOL	①	Update the P/N	26.01.2019	Segal			
X.	±2.0°	②	Drawn	21.11.2018	Segal			
.X	±1.0°							
Angle	TOL	Id.	Modification	Date	Name			

ASSMANN WSW-No. ① A-M08A04MOE10002BK00	
Drawing-No. ASS 8410 CA	rev01
Replace	Sheet

1

2

3

4

5

6

7