

ERO610T332MTCR

Aliases (C824TC332M440X, ERO610RK4330MTCR)

Obsolete

ERO610 SFTY X1-440 Y2-250, Ceramic, 3300 pF, 20%, 440 VAC (X1), 250 VAC (Y2), Y5U, Lead Spacing = 7.5mm



The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

Click [here](#) for the 3D model.

Dimensions	
D	10mm MAX
T	4.5mm MAX
S	7.5mm +0.8/-0.2mm
HO	16mm +/-0.5mm
F	0.6mm +/-0.05mm
A	5mm NOM
V	1.4mm +/-0.5mm

Packaging Specifications	
Packaging	T&R, HO = 16mm, Component Pitch = 12.7mm

General Information	
Series	ERO610 SFTY X1-440 Y2-250
Style	Radial Disc
Description	Ceramic Single Layer Safety Disc Capacitors
RoHS	Yes
Termination	Tin
Qualifications	UL, CSA, CAN, ENEC, VDE
AEC-Q200	No
Notes	Please See Bulletin For Taping Information. HO Dimension Refers to Seating Plane To Center Hole of Tape.

Specifications	
Capacitance	3300 pF
Capacitance Tolerance	20%
Voltage AC	440 VAC (X1), 250 VAC (Y2)
Temperature Range	-40/+125°C
Temperature Coefficient	Y5U
Dissipation Factor	2.5%
Insulation Resistance	6 GOhms
Safety Class	X1/Y2