



- 2 Type**
- D** Consisting of three parts
 - Z** Consisting of two parts

Metric table



Dimensions in: millimeters - inches

s	b	d ₁ Thread	d ₂ Pin	h ₁	h ₂	l ₁	l ₂	l ₃	l ₄ max.	l ₅	l ₆	m ₁	m ₂
12 0.47	15 0.59	M 6	6 0.24	39.2 1.54	25.6 1.01	10 0.39	5 0.20	14 0.55	9 0.35	10 0.39	5 0.20	27.2 1.07	13.6 0.54
16 0.63	20 0.79	M 8	8 0.31	49 1.93	32.5 1.28	14 0.55	8 0.31	22 0.87	16 0.63	14 0.55	8 0.31	33 1.30	16.5 0.65

Specification

- Body
Steel, zinc plated, blue passivated finish
- Pin
Brass, nickel-plated
- Washers
Brass, nickel-plated
- Hexagon nut ISO 4032
Steel, zinc plated, blue passivated finish
- Serrated washer DIN 6797
Steel, zinc plated, blue passivated finish
- RoHS compliant

Information

GN 129 hinges are used for hatch type doors. The two part hinge allows the door to be unHINGED. In the two-part design, the door can be unHINGED with two identically arranged hinges. The three-part hinges, which generally cannot be unHINGED and are mounted inside are suitable for doors and flaps, which as anti-tamper precaution must not be dismountable from the outside.

see also...

- List of Hinge Types
- Hinges GN 129.2 (Steel or Stainless Steel)
- Hinges GN 129.3 (Steel)

<p>How to order</p> <p>GN 129-16-D</p>	1 Square s
	2 Type