

## AGH360 Series

360 Watts

### Data Sheet

**Total Power:** 360 Watts  
**Input Voltage:** 36 - 75 V  
**# of Outputs:** Single

### SPECIAL FEATURES

- 2:1 Wide input range
- Optimised for high density, small space applications
- Low ripple and noise
- Fixed switching frequency
- High efficiency
- High capacitive load capability
- Basic insulation system
- Pre-bias start-up capability
- Openframe structure with Baseplate option

### SAFETY

- UL, cUL: UL60950
- TUV/CE: IEC/EN60950



### Electrical Specifications

#### Input

Input range:	36 - 75 VDC
Efficiency:	12Vo

#### Output

Voltage tolerance:	+/-2.5%
Line regulation:	+/- 0.2%
Load regulation:	+/- 0.2%
Noise/ripple:	120mV
Over voltage protection: Over temperature protection:	Auto-restart
Switching frequency:	145 KHz
Temperature coefficient:	±0.02/°C

#### Isolation

I/O isolation:	1500 VDC min.
----------------	---------------

### Environmental Specifications


Operating ambient temperature range:	-40°C to +85 °C
Storage temperature:	-55 °C to +125 °C
Humidity:	5% to 95% (non-condensing)
MTBF:	1.5 Million hours
RoHS Compliant	

### Ordering Information


Model number	Input voltage	Output voltage	Power
AGH360-48S12-6L	36 - 75 Vin	12V @ 30A	360W
AGH360-48S12B-6L	36 - 75 Vin	12V @ 30A	360W
AGH360-48S12P-6L	36 - 75 Vin	12V @ 30A	360W
AGH360-48S12PB-6L	36 - 75 Vin	12V @ 30A	360W

- Standard version is negative enable
- "-6" = 3.8mm pin length
- "-L" = RoHS6 compliance
- "-P" = Positive enable
- "-B" = Baseplate

### Mechanical Drawings



Side view



Load board

Unit: mm[inch]

Bottom view: pin on upside

Tolerance: X.Xmm ± 0.5mm[X.X in. ± 0.02in.]

X.XXmm ± 0.25mm[X.XX in. ± 0.01in.]

## Pin Assignments

Pin No.	Name	Function
1	Vin+	Positive input terminal
2	Remote ON/OFF	ON/OFF control terminal
3	Case	Case input terminal
4	Vin-	Negative input terminal
5	Vo-	Negative output terminal
6	Sense-	Negative remote sense
7	Trim	Output voltage trim
8	Sense+	Positive remote sense
9	Vo+	Positive output terminal

**Notes:**

1. All specifications are subject to change without notice. Mechanical drawings are for reference only.
2. Warranty: 2 years
3. Label and logo appearance may vary from what is shown on mechanical drawings.

## WORLDWIDE OFFICES

**Americas**

2900 South Diablo Way  
Suite B100  
Tempe, AZ 85282, USA  
+1 888 412 7832

**Europe (UK)**

Ground Floor Offices, Barberry House  
4 Harbour Buildings, Waterfront West  
Brierley Hill, West Midlands  
DY5 1LN, UK  
+44 (0) 1384 842 211

**Asia (HK)**

14/F, Lu Plaza  
2 Wing Yip Street  
Kwun Tong, Kowloon  
Hong Kong  
+852 2176 3333

**ARTESYN™**  
An Advanced Energy Company

[www.artesyn.com](http://www.artesyn.com)

Artesyn Embedded Technologies, Artesyn Embedded Power, Artesyn, and all Artesyn related logos are trademarks and service marks of Artesyn Embedded Technologies, Inc. All other names and logos referred to are trade names, trademarks, or registered trademarks of their respective owners. Specifications are subject to change without notice. © 2019 Artesyn Embedded Technologies, Inc. All rights reserved. For full legal terms and conditions, please visit [www.artesyn.com/legal](http://www.artesyn.com/legal).

For more information: [www.artesyn.com](http://www.artesyn.com)  
For support: [productsupport.ep@artesyn.com](mailto:productsupport.ep@artesyn.com)