




VMDTC125-55-M16-70-Z

Ruland VMDTC125-55-M16-70-Z, Vibration Isolation Mount, 125mm OD, M16 Tapped Holes, 16mm Tapped Hole Depths, 55mm Height, 70 Shore A Natural Rubber Jacket, Steel



Description

Ruland VMDTC125-55-M16-70-Z is a vibration isolation mount with two tapped holes. It has a 125mm outside diameter, M16 tapped holes, 16mm tapped hole depths, and 55mm height. This vibration isolation mount is used to dampen shock loads and reduce noise and wear on industrial equipment such as motors, conveyors, compressors, fans, or pumps which allows for a safer and more pleasant working environment. It is often referred to as a sandwich mount or rubber buffer because it functions as shock or vibration isolator sandwiched between two machine components or surfaces. VMDTC125-55-M16-70-Z can be mounted to the system by threading it onto an existing stud on the components. The rubber jacket is made from natural rubber which has good elasticity and is well suited for most industrial equipment. It has 70 Shore A hardness for the greatest rigidity and load capacity. The zinc plated steel body allows for high strength and is suitable for most industrial applications. VMDTC125-55-M16-70-Z is manufactured by Otto Ganter, inventoried by Ruland, and RoHS3 compliant.

Product Specifications

Outer Diameter (OD)	4.92 in (125 mm)	Height (H1)	2.17 in (55 mm)
Thread (TH)	M16 x 2.0	Plate Thickness (PT)	0.12 in (3 mm)
Tapped Hole Depth (LT)	0.63 in (16.1 mm)	Spring Rate	18186.83 lb/in (3185 N/mm)
Shore Hardness	70A (+/- 5)	Max Deflection	0.31 in (7.9 mm)
Max Axial Load	5620.23 lb (25000 N)	Geometry	Cylindrical
Rubber Material	Natural Rubber	Metal Material	Zinc Plated Steel
Metallic Body Finish	Zinc-Plated	Country of Origin	Hungary
Weight (lbs)	2.923300	UPC	634529355404
Tariff Code	4016.99.6000	UNSPC	31162804
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		