

Data sheet | Item number: 787-2805


DC/DC Converter; 24 VDC input voltage; 12 VDC output voltage; 0.5 A output current; DC OK contact



www.wago.com/787-2805



DC O.K.	1		5	n.c.
GND	2		6	n.c.
Vout+	3	OUT	7	Vin+
GND	4	IN	8	GND



Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.



Item description

Features:

- DC/DC converter in a compact 6 mm housing
- DC/DC converters (787-28xx) supply devices with 5, 10, 12 or 24 VDC from a 24 or 48 VDC power supply with an output power up to 12 W.
- Output voltage monitoring via DC OK signal output
- Can be commoned with 857 and 2857 Series devices
- Comprehensive range of approvals for multiple applications

Data

Technical data

Input

Nominal input voltage $U_{i\text{nom}}$	DC 24 V
Input voltage range	DC 15 ... 30 V
Nominal mains frequency range	0 Hz
Input current I_i	≤ 0.5 A
Inrush current	≤ 0.5 A (at nominal input voltage)

Output

Nominal output voltage $U_{o\text{nom}}$	DC 12 V
Output voltage range	± 2 %
Nominal output current $I_{o\text{nom}}$	0.5 A
Nominal output power	6 W
Residual ripple	≤ 20 mV (peak-to-peak)

Signaling and Communication

Signaling	1 x LED DC OK (green) 1 x Short circuit LED (red) 1 x Active signal output (U_i , max. 4 mA)
Operation status indicator	Green LED (U_o) Red LED (short circuit)

Efficiency/power losses

Power loss P_l	≤ 0.21 W; ≤ 0.7 W (nominal load)
------------------	--

Subject to changes. Please also observe the further product documentation!



Efficiency (typ.)	90 % (at nominal input voltage and nominal output)
-------------------	--

Circuit protection

Internal fuse	No
---------------	----

Safety and protection

Protection class	III
Protection type	IP20; per EN 60529
Reverse voltage protection	yes
Pollution degree	2
Short-circuit-protected	Yes
Open-circuit-proof	Yes
Parallel operation	No
Series operation	No
MTBF	> 1,800,000 h

Connection data

Number of jumper slots	8
Connection technology	Push-in CAGE CLAMP®
WAGO connector	WAGO 857 Series
Solid conductor	0.08 ... 2.5 mm ² / 28 ... 14 AWG
Fine-stranded conductor	0.34 ... 2.5 mm ² / 22 ... 14 AWG
Strip length	9 ... 10 mm / 0.35 ... 0.39 inches

Physical data

Width	6 mm / 0.236 inches
Height	94 mm / 3.701 inches
Depth from upper-edge of DIN-rail	97.8 mm / 3.85 inches

Mechanical Data

Mounting type	DIN-35 rail
---------------	-------------

Material Data

Fire load	0.418 MJ
Weight	48.6 g

Subject to changes. Please also observe the further product documentation!



Environmental requirements

Ambient temperature (operation)	-25 ... +70 °C
Ambient temperature (storage)	-40 ... +85 °C
Relative humidity	95% (no condensation permissible)
Derating	No derating

Standards and specifications

Conformity marking	CE
Standards/specifications	EN 61000-6-2 EN 61000-6-3 EN 60950-1 UL 61010-2-201

Commercial data

eCl@ss 10.0	27-04-07-01
eCl@ss 9.0	27-04-07-01
ETIM 8.0	EC002540
ETIM 7.0	EC002540
PU (SPU)	1 pcs
Packaging type	bag
Country of origin	DE
GTIN	4055143407045
Customs tariff number	85044083900

Environmental Product Compliance



CAS-No.	11120-22-2 1303-86-2 1317-36-8 7439-92-1
REACH Candidate List Substance	Diboron trioxide Lead Lead monoxide Lead silicate
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c) 7(a) 7(c)-I 7(c)-II
SCIP notification number (Austria)	4f2a43e4-a730-4da6-863a-5a38b11c0458

Subject to changes. Please also observe the further product documentation!


SCIP notification number (Belgium)	f9285629-a82b-482e-9934-56caaa89bd90
SCIP notification number (Bulgaria)	aa1c2089-ca90-475b-b065-b290f8c47c73
SCIP notification number (Czech Republic)	e4407a61-44ef-46f6-8b71-5957fb1b0e35
SCIP notification number (Denmark)	62e3f530-0083-4301-a58f-c18079aaac67
SCIP notification number (Finland)	b5859d05-b7e1-4a35-a43a-cf33af17f955
SCIP notification number (France)	9a8251e6-a882-4123-987f-3af679ef6e75
SCIP notification number (Germany)	6edaf339-2ec1-4a85-bfcf-c4ac37d4e41b
SCIP notification number (Hungary)	50511142-efbe-4d96-bb7d-4eb00b7c1b98
SCIP notification number (Italy)	7c3519fd-876f-4af4-a334-e0f41b17ffce
SCIP notification number (Netherlands)	f84285ba-e8f4-418f-8037-d27c744e1818
SCIP notification number (Poland)	91abfe2e-594d-4cbf-9277-a9a191349087
SCIP notification number (Romania)	a5085aab-1513-44f7-a544-88b3170333b2
SCIP notification number (Sweden)	7ecaaaff-70ab-45de-8e2c-ff4a34524af3

Approvals / Certificates

General approvals


Logo	Approval	Additional Approval Text	Certificate name
	EAC Brjansker Zertifizierungsstelle	TP TC 020/2011	EAC_Certificate_RU_C-DE.AM02.B.00115_19
	UL Underwriters Laboratories Inc. (ORDINARY LOCATIONS)	UL 61010-2-201	E175199 Vol3 Sec1

Declarations of conformity and manufacturer's declarations

Logo	Approval	Additional Approval Text	Certificate name
	EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-










Optional accessories

Marking accessories

Marking strip			
	Item no.: 2009-110 Marking strips; for Smart Printer; on reel; not stretchable; plain; snap-on type; white		www.wago.com/2009-110


Subject to changes. Please also observe the further product documentation!

Marker

	Item no.: 2009-115 WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white	www.wago.com/2009-115
	Item no.: 793-501 WMB marking card; as card; not stretchable; plain; snap-on type; white	www.wago.com/793-501
	Item no.: 793-502 WMB marking card; as card; MARKED; 1 ... 10 (10x); not stretchable; Horizontal marking; snap-on type; white	www.wago.com/793-502
	Item no.: 793-503 WMB marking card; as card; MARKED; 11 ... 20 (10x); not stretchable; Horizontal marking; snap-on type; white	www.wago.com/793-503
	Item no.: 793-504 WMB marking card; as card; MARKED; 21 ... 30 (10x); not stretchable; Horizontal marking; snap-on type; white	www.wago.com/793-504
	Item no.: 793-505 WMB marking card; as card; MARKED; 31 ... 40 (10x); not stretchable; Horizontal marking; snap-on type; white	www.wago.com/793-505
	Item no.: 793-506 WMB marking card; as card; MARKED; 41 ... 50 (10x); not stretchable; Horizontal marking; snap-on type; white	www.wago.com/793-506
	Item no.: 793-566 WMB marking card; as card; MARKED; 1 ... 50 (2x); not stretchable; Horizontal marking; snap-on type; white	www.wago.com/793-566
	Item no.: 793-5501 WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; white	www.wago.com/793-5501

Tool

Operating tool

	Item no.: 210-720 Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured	www.wago.com/210-720
--	--	--

Downloads

Documentation

Bid Text

787-2805 X81 - Datei	2019 Feb 19	xml 5.8 kB	Download
787-2805 doc - Datei	2016 Jan 11	doc 35.3 kB	Download

Subject to changes. Please also observe the further product documentation!



787-2805 pdf - Datei	2016 Jan 11	pdf 91.9 kB	Download
-------------------------	-------------	----------------	----------

787-2805 docx - Datei	2016 Jan 11	docx 20.4 kB	Download
--------------------------	-------------	-----------------	----------

Instruction Leaflet

DC/DC-Wandler	V 1.1.1 2020 Mar 31	pdf 2.4 MB	Download
---------------	------------------------	---------------	----------

Additional Information

Disposal and Recycling Electrical and electronic equipment, Batteries, Packaging	V 1.1.0 2022 Aug 18	pdf 2.2 MB	Download
---	------------------------	---------------	----------

CAD/CAE-Data

CAD data

2D/3D Models 787-2805	URL	Download
-----------------------	-----	----------

CAE data

EPLAN Data Portal 787-2805	URL	Download
----------------------------	-----	----------

WSCAD Universe 787-2805	URL	Download
-------------------------	-----	----------

ZUKEN Portal 787-2805	URL	Download
-----------------------	-----	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 787-2805 DC/DC Converter; 24 VDC input voltage; 12 VDC output voltage; 0.5 A output current; DC OK contact	URL	Download
---	-----	----------

Installation Notes

Subject to changes. Please also observe the further product documentation!