



Main

Range	ClimaSys
Product name	ClimaSys CV
Product or Component Type	Fan
Type of filter	Standard
Flow rate	Free flow rate with standard filter 10038.72 Gal/hr(US) (38 m ³ /h) 50 Hz Free flow rate with standard filter 10302.89 Gal/hr(US) (39 m ³ /h) 60 Hz
[Us] rated supply voltage	150...250 V
Input voltage	230 V 50/60 Hz

Complementary

Absorbed power	4.5 W 50 Hz 4.8 W 60 Hz
Line Rated Current	0.16 A 50 Hz 0.17 A 60 Hz
Noise level < at	40...41 dB
Bearing type	Ball
Height	External 5.39 in (137 mm)
Width	External 4.61 in (117 mm)
Depth	External 1.93 in (49 mm)
Cut-out dimensions	92 x 92 mm
Net Weight	0.49 lb(US) (0.22 kg)
Material	Outlet grille injected thermoplastic (ASA PC)
Color	Outlet grille Gray RAL 7035)
Ambient Air Temperature for Operation	14...158 °F (-10...70 °C)
Ambient Air Temperature for Storage	-40...158 °F (-40...70 °C)
Maximum pressure	29 Pa flow rate 0 m ³ /h
Connections - Terminals	Cable
IP degree of protection	IP54
Device composition	1 axial motor 2 protective grille on the front and rear surfaces 1 filter front of axial motor 1 outlet grille front 1 cut-out template
Condition of use	Outside temperature must be 5 °C lower than inside temperature Flow rates depends on the work point, see ProClima software Surrounding environment must be relatively clean Filter must be cleaned and replaced regularly Overfrequent filter replacement should be avoided

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480151163
Nbr. of units in pkg.	1
Package weight(Lbs)	9.88 oz (280.0 g)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.76 in (7.0 cm)
Package 1 width	4.72 in (12.0 cm)
Package 1 Length	5.71 in (14.5 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	34
Package 2 Weight	24.12 lb(US) (10.94 kg)
Package 2 Height	23.62 in (60.0 cm)
Package 2 width	15.75 in (40.0 cm)
Package 2 Length	11.02 in (28.0 cm)
Unit Type of Package 3	P12
Number of Units in Package 3	544
Package 3 Weight	418.88 lb(US) (190.0 kg)
Package 3 Height	37.40 in (95.0 cm)
Package 3 width	31.50 in (80.0 cm)
Package 3 Length	47.24 in (120.0 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------