





APPROVED: _____
 DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	4/15/05	
A		REDRAWN	4/9/12	
B		REVISED SPEC.	6/27/14	AY/CH
C		UPDATED DRAWING	7/25/18	HR/MY



SPECIFICATIONS:

Material:
 Insulator: PBT, glass reinforced, rated UL 94V-0
 Insulator color: Black
 Contacts: Brass
 Shell: Steel, Tin plated
 Boardlock: Brass, Tin plated
 Plating:
 Gold over Nickel underplate on contact area
 Electrical:
 Voltage rating: 250 VAC/rms
 Current rating: 3 Amp
 Contact resistance: 20 mohms
 Insulation resistance: 1000 Mohms @ 500 VDC
 Dielectric withstanding voltage: 1,000 VAC for 1 minute
 Temperature Rating:
 -55°C to +85°C
 Environmental:
 Lead free, RoHS compliant



DXXX	NO. OF CONTACTS	DIMENSIONS				
		A	B	C	D	E
DE09	9	.643 [16.33]	.984 [24.99]	1.213 [30.81]	.756 [19.20]	.436 [11.08]
DA15	15	.972 [24.70]	1.311 [33.30]	1.543 [39.20]	1.091 [27.70]	.763 [19.39]
DB25	25	1.512 [38.40]	1.852 [47.04]	2.089 [53.05]	1.618 [41.10]	1.309 [33.24]
DC37	37	2.157 [54.80]	2.500 [63.50]	2.732 [69.40]	2.256 [57.30]	1.963 [49.86]

UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE INCHES [MM]
 TOLERANCES: EXCEPT AS NOTED
 INCHES HOLES
 .X ±.10 Ø.X ±.10
 .XX ±.020 Ø.XX ±.015
 .XXX ±.015 Ø.XXX ±.010

ADAM TECH INTERCONNECTS
 909 Rahway Avenue,
 Union, NJ 07083
 Phone: 908-687-5000
 Fax: 908-687-5710

APPROVALS		DATE
DRAWN	SS	4/15/05
CHECKED		
APPROVED		

TITLE D-SUB SOCKET, STANDARD PROFILE RIVETED #4-40 STANDOFFS W/BOARDLOCKS		
SIZE X	PART NO. DXXX-ST-1-BL	REV. C
REF: S00087T	SCALE: NTS	SHEET 1 OF 1