



OBSOLETE
 PCR 23936
 JULY 2019

- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 - ▲ 4. CONTACT RATING: 0.1A MAX. @ 28VDC
 5. CONTACT MATERIAL: GOLD
 6. ELECTRICAL LIFE: 200,000 Typical
 7. MECHANICAL LIFE:
1,000,000 CYCLES TYP.
 8. OPERATING TEMP: -20°C TO +70°C
 9. OPERATING FORCE: 300 ± 150 gf
 10. CONTACT RESISTANCE:
100 MILLI-OHM INITIAL TYP. MAX.
 11. INSULATION RESISTANCE:
500VDC, 100 MΩ MIN.
 12. DIELECTRIC STRENGTH:
1000 VAC FOR 1 MINUTE
 13. TRAVEL TO MAKE: 2.20mm ± 0.2 LATCHING
 14. 2002/95/EC (ROHS) COMPLIANT
 15. ▲ DENOTES CRITICAL PARAMETER
 - ▲ 16. LED COLOR: RED: 3 CHIPS; 1.7VDC, @20mA TYP.
GRN: 3 CHIPS; 2.1VDC, @20mA TYP.



G	22339	UPDATED CONTACT RATING	6/7/16	MJR
F	19737	CORRECT TERMINALS	03/07/11	BMA
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE ULP22EEP1RSSCL1GRNRED				
SCALE	DATE	DR	DWG	REV
1.5:1	3/7/2008	BF	B800009	G

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED