

VIEW ON MATING SIDE

∞	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
<	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30

A = 64 CONTACTS L-2,9

Marking	Standard
Performance level	G2/0 = Contact area level2 / Termination tin
Flux proof	no
Fixing clip	no
Dimensions	SDA-85040-0001 sht.1
Technical Data	PS-85042-0001

A	G2/0	a1-32	b1-32
Contact symbol	Perform. level	Contact position number	

ECN 2264 Produkt spec. 96-10-18 KN	REVISIONS	FOR PREVIOUS REVISIONS SEE MRI LIST	
	LTR	A-1	96-10-18 KN
SH. REV.	REVISE ONLY ON CAD SYSTEM	CAD/CAM PROJECT NAME	SHEET NO. DATE
1 OF 1		s8504001 s21	1 OF 1 96/05/15
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			
TITLE			
64 pos. female connector acc. DIN 41612 style B contacts arrangement		MOLEX EUROPE	
MOLEX EUROPE		SHEET NO. DATE	
1 OF 1		1 OF 1 96/05/15	
PART NO.		DWG NO.	
85040-0127		SDA-85040-0127	
SIZE		A	

UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 2°
INCH METRIC

3 PLACE ± .	±
2 PLACE ± .	±
1 PLACE ± .	±

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DESIGN DIMENSION MM IN.

EQUIVALENT DIMENSION MM IN.

IF TWO DIMENSIONS ARE SHOWN, THE UPPER IS THE DESIGN DIMENSION, LOWER IS SECONDARY